

1 BRIAN E. HOLTHUS, ESQ.
2 Nevada Bar No. 2720
3 beh@juwlaw.com
4 JOLLEY URGA WOODBURY & HOLTHUS
5 50 S. Stephanie Street, Suite 202
6 Henderson, Nevada 89012
7 (702) 699-7500 Telephone
8 (702) 699-7555 Facsimile
9
10 Christopher W. Niro (pro hac vice pending)
11 Matthew De Preter (pro hac vice pending)
12 ARONBERG GOLDGEHN DAVIS & GARMISA
13 330 North Wabash Avenue, Suite 1700
14 Chicago, Illinois 60611
15 (312) 828-9600
16 cniro@agdglaw.com
17 cdepreter@agdglaw.com

18 *Attorneys for Plaintiff MPI LLC*

19 **UNITED STATES DISTRICT COURT**
20 **DISTRICT OF NEVADA**

21 MPI LLC

Case No.

22 Plaintiffs,

**COMPLAINT FOR PATENT
INFRINGEMENT**

23 v.

24 SORTING ROBOTICS, INC., and
25 HARRISON BARD an individual doing
26 business as CUSTOM CONES USA,

27 Defendants.

28 Plaintiff, MPI LLC (“MPI”) for its complaint against Defendants Sorting Robotics, Inc.
 (“Sorting Robotics”) and Harrison Bard d/b/a Custom Cones USA (“Custom Cones”) alleges as
 follows:

///
///
///

JOLLEY URGA attorneys
WOODBURY & HOLTHUS at law

50 S. STEPHANIE STREET, SUITE 202, HENDERSON, NV 89012
TELEPHONE: (702) 699-7500 FAX: (702) 699-7555

JOLLEY URGAL
WOODBURY & HOLTHUS
attorneys
at law

50 S. STEPHANIE STREET, SUITE 202, HENDERSON, NV 89012
TELEPHONE: (702) 699-7500 FAX: (702) 699-7555

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

INTRODUCTION

1. This is a civil action for infringement of United States Patent No. 11,130,596 (“the ‘596 Patent”) under the Patent Act, 35 U.S.C. §100 et seq., based on Defendants use, and its contribution to and inducement of others use of its Automated Infused Pre-Roll Machine. A copy of the ‘596 Patent is attached as **Exhibit A**.

2. MPI brings this action ins response to repeated, knowing, and willful infringement by Defendants of MPI’s patent rights in its novel folded packages including pre-rolled cones which is disclosed in the ‘596 Patent.

3. MPI is a company dedicated to building technologies to assist manufacturing and packaging companies make and deliver high quality pre-rolled cones and other packages.

4. MPIs technology is currently being used in connection with the creation of folded packages and pre-rolled cones containing hemp.

THE PARTIES

5. MPI is a limited liability company organized under the laws of the state of Nevada having a place of business at 3645 W. Twain Ave. Las Vegas, Nevada 89103.

6. MPI is the sole owner of all right title and interest in and to the ‘596 Patent by assignment recorded with the United States Patent Office on February 4, 2020, Reel/Frame 051717/0161.

7. Sorting Robotics, Inc. is a company organized under the laws of the state of Delaware with a principal place of business at 7647 Hayvenhurst Ave. Suite 39, Van Nuys, California 91406.

8. Upon information and belief Harrison Bard is an individual, doing business as Custom Cones USA with an address of 7059 S. 190th Street, Kent, WA 98032.

///

JURISDICTION AND VENUE

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

9. This court has subject matter jurisdiction over this patent infringement action pursuant to 28 U.S.C. §§ 1331 and 1338(a).

10. This court has personal jurisdiction over Defendants because Defendants regularly solicit and conduct business in Nevada and engage in other persistent courses of conduct in Nevada.

11. This court also has personal jurisdiction over Defendants because, upon information and belief, Custom Cones commits acts of infringement in Nevada, including but not limited to exhibiting the infringing technology at trade shows taking place in Las Vegas, Nevada, and directly infringing one or more claims of the ‘596 Patent.

12. Further, upon information and belief, Sorting Robotics contributes to and induces the infringement of Custom Cones within Nevada.

13. On or about October 18 – 21, 2021 Custom Cones attended, exhibited and participated in NJBIZCON at the Las Vegas Convention Center.

14. Through Custom Cones website, www.customconesusa.com, Custom Cones and Sorting Robotics at least advertise and offer to sell in Nevada the Automated Infused Pre-Roll Machine for the purpose of manufacturing infringing cones.

15. Venue is proper in this judicial district pursuant to 28 U.S.C. §§ 1391 and 1400 at least because Defendants have committed and continues to commit, acts of infringement in Nevada, including but not limited to making, selling and offering to sell products that infringe one or more claims of the ‘596 Patent.

///

///

///

JOLLEY URGAL attorneys
at law
WOODBURY & HOLTHUS
50 S. STEPHANIE STREET, SUITE 202, HENDERSON, NV 89012
TELEPHONE: (702) 699-7500 FAX: (702) 699-7555

FIRST CLAIM FOR RELIEF
Direct Infringement of the ‘596 Patent
(35 U.S.C. §271(a))

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

16. MPI incorporates by reference the allegations of the preceding paragraphs as if fully recited herein.

17. The ‘596 Patent is valid and enforceable.

18. Upon information and belief, Custom Cones has been, and currently is, directly infringing at least Claim 9 of the ‘596 Patent by making, selling, offering for sale the Automated Infused Pre-Roll Machine (“the Machine”) and pre-rolled cones manufactured and filled using the Machine within the United States.

19. Custom Cones is the registrant of the internet domain customconesusa.com

20. Custom Cones controls the content displayed on the internet website accessible through www.customconesusa.com.

21. At all times relevant, Custom Cones is responsible for uploading and managing the content displayed on the internet website accessible through <https://customconesusa.com/automated-infused-pre-roll-machine/>. (the “Pre-Roll Website”).

22. The Pre-Roll Website is accessible within the State of Nevada.

23. Upon information and belief, customers and prospective customers within this judicial district can access and view the Pre-Roll Website.

24. At all times relevant, through the Pre-Roll Website, Custom Cones demonstrated how the Machine functions to form folded, infused pre-roll packages.

25. On October 19, 2021 counsel for MPI sent a letter to Custom Cones informing them of the issuance of the ‘596 Patent. A true and correct copy of the October 19, 2021 Letter is attached as **Exhibit B**.


JOLLEY URGAL HOLTHUS attorneys at law
WOODBURY & HOLTHUS
50 S. STEPHANIE STREET, SUITE 202, HENDERSON, NV 89012
TELEPHONE: (702) 699-7500 FAX: (702) 699-7555

1 26. In that letter, MPI provided Custom Cones with a representative claim chart
2 showing Custom Cones’ infringement of the ‘596 Patent.

3 27. The letter and claim chart therein provided images of Custom Cones’ product
4 manufacturing.

5 28. Further, MPI requested that Custom Cones stop manufacturing, selling, offering
6 to sell and promoting the Machine and folded packages manufactured using the machine.

7 29. A true and correct reproduction of the Pre-Roll Website is below:



8 Home

Automated Infused Pre-Roll Machine


New Pre-Roll Tech Exclusively From Custom Cones USA!

If you are making infused pre-rolls manually by hand, our automated pre-roll infusing machine will take your production process and infused pre-roll line to the next level! A specially designed and patented reservoir heats up your oil, which is then fed through a medical-grade needle and into the center of your finished pre-rolls. Up to 20 pre-rolls at a time are loaded into a circular cartridge, which rotates under the needle, where a rod of oil is perfectly placed in the center of the pre-roll.

Each Automated Pre-Roll Infusing Machine comes with a tablet, which is used to remotely control all the settings of the infuser machine. The operator is able to specify the exact length of the infused oil rod, as well as the exact location. For example, you can choose to infuse a 30mm rod of oil 10mm above the filter tip! Since our Automated Pre-Roll Infusing machine carefully places the rod of oil in the center, your infused pre-roll will burn perfectly even and smooth. In fact, since the oil is infused in the center, rather than painted on the outside of the pre-roll, the oil starts to get vaporized by the end of the lit pre-roll, which creates a smoother, less harsh smoke.



Sign up for a virtual demo today!



23 30. Through the Pre-Roll Website, Custom Cones provides customers and the public
24 with a detailed description of the Machine.


25 31. A true and correct reproduction of the Pre-Roll Website is shown below:

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28



Overview of Components:

- Infusion Machine: 1x
- Joint Wheel: 6x
- Joint Wheel Lid: 3x
- Infusion Needle: 5x
- Preroll Ejector: 1x



https://customconesusa.com/automated-infused-pre-roll-machine/ Safari 15.0 (16612.1.29.41.4)
November 11, 2021 at 9:17:37 AM 10.16.0

32. Custom Cones, through the Pre-Roll Website provide the product specifications for the Machine.

33. A true and correct reproduction of the Pre-Roll Website product specifications for the Machine is below:

///

///

///

///

///

///

///

///

///

///

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

  [ACCOUNT](#) [CART](#) [833-582-6637](#) | [CONTACT US](#)

[SHOP ALL PRODUCTS](#) [PRE-ROLLED CONES](#) [PRE-ROLLED BLUNTS](#) [PRE-ROLLED TUBES](#) [PRE-ROLL MACHINES](#) [PRE-ROLL PACKAGING](#) [CUSTOM PRE-ROLL PACKAGING](#) [CUSTOM PRE-ROLLED CONES](#)

Product Specifications:

Single Load Capacity.	20 pre-rolls
Infusion Throughput..	800 pre-rolls per hour
• Load capacity is based on standard tapered cone wheels • Throughput is dependent on wheels used and operator efficiency.	
Infusion Dosing Capability	50mg - 1,000mg with 50mg increments
Infusion Materials	Decarbed Concentrates, High Terpene Extract, ▲9 and ▲8 Distillates

Size and Dimensions:

Infusion Machine Weight	110 lbs
Infusion Machine Dimensions	48" x 24" x 66" (W x D x H)
Noise Level	65dB

PRODUCT REQUIREMENTS

Power	700W @110VAC
Ambient Temperature	60°F - 90°F
Internet Connection	WiFi Required

https://customconesusa.com/automated-infused-pre-roll-machine/	Safari 15.0 (16612.1.29.41.4)
November 11, 2021 at 9:19:42 AM	10.16.0

34. Custom Cones, through the Pre-Roll Website, states that the Machine is capable of infusing up to 800 Pre-Rolls Per Hour.

35. The Machine produces a folded package that has a core of fluid.

36. Custom Cones states, through the Pre-Roll Website, that the Machine “Infuses a rod of oil perfectly in the middle of the pre-roll!”

37. A true and correct reproduction of the Pre-Roll Website is below:

///

///

///

///

///

///

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28



INFUSES UP TO
800
PRE-ROLLS PER HOUR

- Reduces labor expenses with a single operator!
- Infuses a rod of oil perfectly in the middle of the pre-roll!
- Works with all common sizes of pre-rolls and blunts!
- Super easy to clean and operate the machine!



<https://customconesusa.com/automated-infused-pre-roll-machine/>
November 11, 2021 at 9:23:55 AM

Safari 15.0 (16612.1.29.41.4)
10.16.0

38. The pre-rolls manufactured, sold, and offered for sale by Custom Cones are folded packages comprised of:

- a. A hollow paper cone having an exterior, an interior, a length, a width, and two ends opposite each other joined by a middle section, where one end is a proximal end, and the other end is a distal end and where the length is greater than the width; and
- b. a filling within the cone;
- c. wherein the distal end comprises approximately a quarter of the length of the cone;
- d. wherein the distal end of the cone terminates at a rim; and
- e. wherein a portion of the distal end is crimped in on itself and folded into the interior of the cone such that the rim of the distal end is held by plastic deformation of the paper within the interior of the cone such that the

1 folded portion of the distal end substantially covers the filling within the
2 cone and forms a circumferential lip of paper at the distal end.

3 f. Additionally, the pre-rolls manufactured by Custom Cones also include an
4 access hole has a diameter that is less than the width of the distal end at
5 every point along the length of the distal end.

6
7 g. Additionally, the pre-rolls manufactured by Custom Cones also include a
8 filling, wherein the filling further comprises plant matter and a core of
9 fluid, the core of fluid being formed along the length of the cone and
10 separated from the paper cone by the plant matter.

11 39. The pre-rolls manufactured by Custom Cones as described in paragraph 35
12 constitute direct infringement of at least Claim 9 of the '596 Patent.

13
14 40. Custom Cones posted the video available (last accessed on November 11, 2021)
15 at: [https://m.facebook.com/CustomConesUSA/videos/las-vegas-bizcon-](https://m.facebook.com/CustomConesUSA/videos/las-vegas-bizcon-2021/426009295804456/?m_entstream_source=timeline&_tn_=-R)
16 [2021/426009295804456/?m_entstream_source=timeline&_tn_=-R](https://m.facebook.com/CustomConesUSA/videos/las-vegas-bizcon-2021/426009295804456/?m_entstream_source=timeline&_tn_=-R).

17 41. Custom Cones attended MJBIZCON 2021 in Las Vegas in October 2021.

18 42. Custom Cones occupied a booth in the central hall of the Las Vegas Convention
19 Center with booth number C6520.

20 43. During MJBIZCON, Custom Cones demonstrated the operation of the Machine.

21 44. During MJBIZCON, Custom Cones advertised, sold, or offered for sale, pre-
22 rolled folded packages as described in Paragraph 35.

23
24 45. On or about August 2, 2021, and at all times relevant, Custom Cones filmed and
25 caused to be uploaded to YouTube.com a video titled: "Automated Pre-Roll Infusion Machine".

26 46. Custom Cones uploaded the video available (last accessed on November 11,
27 2021) at: <https://www.youtube.com/watch?v=xRY1D1UCKQQ>. (the "YouTube Video").
28

1 47. Upon information and belief, Harrison Bard is the individual recorded in the
2 video available at <https://www.youtube.com/watch?v=xRY1DIUCKQQ>.

3 48. The YouTube Video demonstrates the operation of the Machine and the
4 manufacture of folded packages.

5 49. The YouTube Video shows Custom Cones using the Machine to manufacture
6 folded packages as described in Paragraph 35.

7 50. Custom Cones has had knowledge of the ‘596 Patent and its infringement since at
8 least its receipt of the October 19, 2021 letter from counsel for MPI.

9 51. Custom Cones infringement has been knowing, intentional, willful and deliberate.

10 52. Custom Cones infringement has caused substantial and irreparable harm to MPI’s
11 business and property rights. Specifically, as competitors with MPI, Custom Cones’
12 infringement and MPI’s harm will continue unless Custom Cones is enjoined from its
13 infringement pursuant to 35 U.S.C. §283. MPI has no adequate remedy at law.

14 53. Custom Cones deliberate infringement without any reasonable justification makes
15 this an exceptional case, entitling MPI to an award of, inter alia, attorneys fees under 35 U.S.C.
16 §285.

17
18
19
20 **SECOND CLAIM FOR RELIEF**
21 **Contributory Infringement of the ‘596 Patent**
22 **(35 U.S.C. § 271(c))**

23 54. MPI incorporates by reference the allegations of the preceding paragraphs as if
24 fully recited herein.

25 55. Sorting Robotics learned of the technology of the ‘596 Patent on or before its
26 receipt of MPI’s counsel’s letter of October 19, 2021.

27 56. In that letter, MPI’s counsel notified Sorting Robotics of its infringement and
28 Sorting Robotics then continued its infringement despite this knowledge.

- 1 57. Upon information and belief, Sorting Robotics manufactures, sells, offers for sale,
2 the Machine.
- 3 58. Sorting Robotics is the registrant of the internet domain sortingrobotics.com.
- 4 59. Sorting Robotics controls the content on the website available through
5 www.sortingrobotics.com (the “SR Website”).
- 6
- 7 60. The SR Website can be viewed and accessed by individuals in the state of
8 Nevada.
- 9 61. The SR Website is not a passive informational website.
- 10 62. Customers, including residents of the state of Nevada, can purchase products
11 directly through the SR Website.
- 12 63. Upon information and belief, Sorting Robotics has sold, or offered for sale
13 products to customers in the state of Nevada.
- 14 64. Sorting Robotics is the manufacturer of, among other things, an Automated Pre-
15 Roll Infusion Machine.
- 16 65. The Automated Pre-Roll Infusion Machine manufactured by Sorting Robotics has
17 the name Jiko.
- 18 66. Upon information and belief, Sorting Robotics has manufactured, sold, offered
19 for sale, advertised Jiko in the United States.
- 20 67. Upon information and belief, the pre rolls manufactured by Custom Cones as
21 described in Paragraph 35 are, in fact, manufactured by a Jiko machine manufactured by Sorting
22 Robotics.
- 23 68. On or about October 19, 2021 counsel for MPI sent Sorting Robotics a letter
24 informing them of their infringement. A true and correct copy of that letter is attached as
25 **Exhibit C.**
- 26
- 27
- 28

1 69. These actions and Sorting Robotics’ knowledge of the ’596 Patent and its
2 infringement of the patent show that Sorting Robotics sells or offers to sell its Jiko Machine
3 knowing it is especially made or especially adapted for practicing the invention of the ’596
4 Patent and is not a staple article or commodity of commerce suitable for substantial non-
5 infringing use.

6 70. Specifically, the Jiko is designed for use to create folded packages covered by at
7 least Claim 9 of the ’596 Patent as described in Paragraph 35. The Jiko is designed for this
8 infringing purpose and is not suited for other purposes.

9 71. Upon information and belief, Sorting Robotics has been, and currently is,
10 indirectly infringing at least Claim 9 of the ’596 Patent by actively contributing to its customers’
11 direct infringement within the United States.

12 72. Sorting Robotics’ actions constitute contributory infringement in violation of 35
13 U.S.C. §271(c).

14 73. Sorting Robotics’ infringement has been knowing, intentional, willful, and
15 deliberate.

16 74. Sorting Robotics’ infringement has caused substantial and irreparable harm to
17 MPI’s business and property rights. Specifically, as competitors with MPI, Sorting Robotics
18 infringement has caused and will continue to cause lost sales, lost customers, and a decrease in
19 market share.

20 75. MPI will continue to suffer harm unless Sorting Robotics is enjoined from its
21 infringement pursuant to 35 U.S.C. §283. MPI has no adequate remedy at law.

22 76. Sorting Robotics’ deliberate infringement without any reasonable justification
23 makes this an exceptional case, entitling MPI to an award of attorneys fees under 35 U.S.C.
24 §285.

THIRD CLAIM FOR RELIEF
Inducing Infringement of the ‘596 Patent
(35 U.S.C. § 271(b))

1
2
3 77. MPI incorporates by reference the allegations of the preceding paragraphs as if
4 fully recited herein.

5
6 78. Upon information and belief, Sorting Robotics has been, and currently is,
7 indirectly infringing at least Claim 9 of the ‘596 Patent by actively and knowingly inducing its
8 customers to use the Jiko machine within the United States.

9 79. Sorting Robotics encourages this infringing activity by selling, leasing, or
10 providing the Jiko machine to its customers, and providing instructions and related
11 documentation, materials, marketing, advertising, training, or support for the operation of its Jiko
12 machine. Sorting Robotics has done this with knowledge of the ‘596 Patent.


13
14 80. As described above, Sorting Robotics has had knowledge of the ‘596 Patent since
15 at least its receipt of the October 19, 2021 letter from counsel for MPI.

16 81. Despite its knowledge of the ‘596 Patent, Sorting Robotics continued to sell the
17 infringing Jiko machine and has continued to offer to sell and advertise it through the SR
18 Website.

19 82. For example, Sorting Robotics provides a video through the SR Website
20 demonstrating the operation of the Jiko machine. The video is available at
21 <https://www.sortingrobotics.com/jiko> (Last accessed on November 12, 2021).

22
23 83. Further, Sorting Robotics Founder and CEO Nothal Partansky appears on a
24 separate video available through the SR Website and also <https://vimeo.com/580394014> (Last
25 accessed on November 12, 2021) explaining the Jiko machine and, specifically “the end product
26 of what is produced after a pre-roll is infused by a Jiko Machine.” A true and correct image of
27 that video is reproduced below:
28

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28



84. Sorting Robotics’ active selling, instructions, videos, documentation and related materials instruct at least one of its customers, including but not limited to Custom Cones, in the United States to use the Jiko machine to manufacture folded packages as claimed in at least Claim 9 of the ‘596 Patent.

85. Sorting Robotics instructs its customers to use the Jiko machine to create folded packages described in Paragraph 35, above that also feature an access hole has a diameter that is less than the width of the distal end at every point along the length of the distal end.

86. Further, Sorting Robotics instructs its customers to use the Jiko machine to create folded packages described in Paragraph 35, above that also include a filling, wherein the filling further comprises plant matter and a core of fluid, the core of fluid being formed along the length of the cone and separated from the paper cone by the plant matter.

1 87. Sorting Robotics encourages this activity even though it actually knew,
2 reasonably should have known, or willfully blinded itself to, the fact that MPI has a patent on the
3 relevant technology.

4 88. Sorting Robotics' acts constitutes active inducement of patent infringement in
5 violation of 35 U.S.C. §271(b).

6 89. Sorting Robotics' infringement has been knowing, intentional, willful, and
7 deliberate. For example, Sorting Robotics learned of the '596 Patent and continued to sell, offer
8 for sale the Jiko machine.

9 90. Sorting Robotics' infringement has caused substantial and irreparable harm to
10 MPI's business and proprietary rights. Specifically, as competitors with MPI, Sorting Robotics
11 infringement has caused and will continue to cause lost sales, lost customers, and a decrease in
12 market share. MPI will continue to suffer this harm unless Sorting Robotics is enjoined from its
13 infringement pursuant to 35 U.S.C. §283. MPI has no adequate remedy at law.

14 91. Sorting Robotics deliberate infringement without any reasonable justification
15 makes this an exceptional case, entitling MPI to an award of attorneys fees under 35 U.S.C.
16 §285.

17
18
19 **FOURTH CLAIM FOR RELIEF**
20 **Direct Infringement of the '596 Patent**
21 **(35 U.S.C. § 271(a))**


22 92. MPI incorporates by reference the allegations of the preceding paragraphs as if
23 fully recited herein.

24 93. Upon information and belief, Sorting Robotics has been, and currently is, directly
25 infringing at least Claim 9 of the '596 Patent by manufacturing pre-rolls using the Jiko machine
26 within the United States.

1 94. Sorting Robotics has done this and promoted the use of the pre-rolls with
2 knowledge of the '596 Patent.

3 95. On information and belief, despite its knowledge of the '596 Patent, Sorting
4 Robotics continues to manufacture pre-rolls using the Jiko machine.

5 96. Sorting Robotics Founder and CEO Nohtal Partansky appears in a video available
6 through the SR Website and also <https://vimeo.com/580394014> (Last accessed on November 12,
7 2021) explaining the Jiko machine and, specifically “the end product of what is produced after a
8 pre-roll is infused by a Jiko Machine.” A true and correct image of that video is reproduced
9 below:
10



27 97. Sorting Robotics’ manufactures the folded package using the Jiko machine as
28 claimed in at least Claim 9 of the '596 Patent.

JOLLEY URGAL attorneys
at law
WOODBURY & HOLTHUS
50 S. STEPHANIE STREET, SUITE 202, HENDERSON, NV 89012
TELEPHONE: (702) 699-7500 FAX: (702) 699-7555

1 98. Sorting Robotics uses the Jiko machine to manufacture folded packages as
2 described in Paragraph 35, above that also feature an access hole has a diameter that is less than
3 the width of the distal end at every point along the length of the distal end.

4 99. Sorting Robotics uses the Jiko machine to manufacture folded packages as
5 described in Paragraph 35, above that also include a filling, wherein the filling further comprises
6 plant matter and a core of fluid, the core of fluid being formed along the length of the cone and
7 separated from the paper cone by the plant matter.
8

9 100. Sorting Robotics has manufactured the infringing folded packages even though it
10 actually knew, reasonably should have known, or willfully blinded itself to, the fact that MPI has
11 a patent on the relevant technology.

12 101. Sorting Robotics' acts constitutes direct infringement in violation of 35 U.S.C.
13 §271(a).
14

15 102. Sorting Robotics' infringement has been knowing, intentional, willful, and
16 deliberate. For example, Sorting Robotics learned of the '596 Patent and continued to
17 manufacture folded packages using the Jiko machine.

18 103. Sorting Robotics' infringement has caused substantial and irreparable harm to
19 MPI's business and proprietary rights. Specifically, as competitors with MPI, Sorting Robotics
20 infringement has caused and will continue to cause lost sales, lost customers, and a decrease in
21 market share. MPI will continue to suffer this harm unless Sorting Robotics is enjoined from its
22 infringement pursuant to 35 U.S.C. §283. MPI has no adequate remedy at law.

23 104. Sorting Robotics deliberate infringement without any reasonable justification
24 makes this an exceptional case, entitling MPI to an award of attorneys fees under 35 U.S.C.
25 §285.
26

27 ///
28

PRAYER FOR RELIEF

WHEREFORE, MPI respectfully requests that this Court enter:

a. Judgment that Custom Cones has infringed at least one claim of the ‘596 Patent in violation of 35 U.S.C. § 271(a);

b. Judgment that Sorting Robotics has directly infringed, actively induced infringement of, and contributorily infringed at least one claim of the ‘596 Patent in violation of 35 U.S.C. § 271(a), (b) and (c);

c. A permanent injunction enjoining Custom Cones and its employees, agents, officers, directors, attorneys, successors, affiliates, subsidiaries, and assigns, and all other persons acting in active concert and participation with any of the foregoing entities, from infringing, contributing to the infringement of, or inducing the infringement of the ‘596 Patent;

d. A permanent injunction enjoining Sorting Robotics and its employees, agents, officers, directors, attorneys, successors, affiliates, subsidiaries, and assigns, and all other persons acting in active concert and participation with any of the foregoing entities, from infringing, contributing to the infringement of, or inducing the infringement of the ‘596 Patent;

///

///

///

///

///

///

///

///

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

JOLLEY URGAL HOLTHUS attorneys at law
WOODBURY & HOLTHUS
50 S. STEPHANIE STREET, SUITE 202, HENDERSON, NV 89012
TELEPHONE: (702) 699-7500 FAX: (702) 699-7555

1 e. A declaration that this case is exceptional under 35 U.S.C. § 285 and an order
2 awarding MPI its reasonable attorneys fees and costs; and

3 f. Any such other and further relief as this Court deems just and proper.
4

5 DATED this 15th day of November 2021.
6

7 Respectfully submitted,

8 JOLLEY URGA WOODBURY & HOLTHUS
9

10 Brian E. Holthus, Esq.

11 BRIAN E. HOLTHUS, ESQ.

12 Nevada Bar No. 2720

13 50 S. Stephanie Street, Suite 202

14 Henderson, Nevada 89012

15 Christopher W. Niro (pro hac vice pending)

16 Matthew De Preter (pro hac vice pending)

17 ARONBERG GOLDGEHN DAVIS & GARMISA

18 330 North Wabash Avenue, Suite 1700

19 Chicago, Illinois 60611

20 (312) 828-9600

21 cniro@agdglaw.com

22 cdepreter@agdglaw.com

23 *Attorneys for Plaintiff MPI LLC*
24
25
26
27
28

EXHIBIT A



(12) **United States Patent**
Holderman et al.

(10) **Patent No.:** **US 11,130,596 B2**
(45) **Date of Patent:** **Sep. 28, 2021**

(54) **FOLDED PACKAGE**

(2013.01); **B65B 43/56** (2013.01); **B65B 43/60** (2013.01); **B65B 31/027** (2013.01); **B65D 21/0233** (2013.01); **B65D 71/06** (2013.01); **B65D 77/14** (2013.01); **B65G 47/847** (2013.01); **B65G 47/88** (2013.01)

(71) Applicant: **MPI, LLC**, Las Vegas, NV (US)

(72) Inventors: **Mark W. Holderman**, Spokane, WA (US); **Gregory A. Russell**, Spokane, WA (US)

(58) **Field of Classification Search**
CPC **B65B 1/04**; **B65B 3/04**; **B65B 7/02**; **B65B 7/28**; **B65B 37/02**
USPC **53/267**, **270**, **297**, **467**, **471**
See application file for complete search history.

(73) Assignee: **MPI, LLC**, Las Vegas, NV (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 338 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

(21) Appl. No.: **16/380,194**

2,925,347 A 2/1960 Cummings
2,982,074 A 5/1961 Shiu
(Continued)

(22) Filed: **Apr. 10, 2019**

(65) **Prior Publication Data**

US 2020/0010284 A1 Jan. 9, 2020

Related U.S. Application Data

(63) Continuation of application No. PCT/US2019/026711, filed on Apr. 10, 2019.
(Continued)

OTHER PUBLICATIONS

Premium Vials, https://www.premiumvials.com/cones-coolbox-120-original-filling-machine-98mm-109mm/?gclid=Cj0KC-QiAsvTxBRDkARIsAH4W_j_KMdv7et3w4Ow2EcsRWqUN_iPRYNfKH3npHZIX-v3f_ISGOINrUdgaAsoQEALw_wcB, 7 pages, USA.
(Continued)

(51) **Int. Cl.**

B65B 1/04 (2006.01)
B65B 7/02 (2006.01)
B65B 7/28 (2006.01)
B65B 5/06 (2006.01)
B65B 43/50 (2006.01)
B65B 43/60 (2006.01)
B65B 43/44 (2006.01)
B65B 37/00 (2006.01)
B65B 43/56 (2006.01)
B65D 21/02 (2006.01)

Primary Examiner — Douglas A Hess
(74) *Attorney, Agent, or Firm* — Aronberg Goldgehn Davis and Garmisa


(57) **ABSTRACT**

The technology described herein generally relates to an automated packaging apparatus and system that packages loose particles into a conical container as well as the final folded packages. More specifically, loose plant matter, such as crumbled dried leaves, are supplied to successive paper cones. The apparatus packs the crumbled leaves into the cones, closes the wide top portion of the cone into a precise shape, and then runs a quality control check to ensure that the final filled cone meets preset specifications.

(52) **U.S. Cl.**

CPC **B65B 1/04** (2013.01); **B65B 5/06** (2013.01); **B65B 7/02** (2013.01); **B65B 37/00** (2013.01); **B65B 43/44** (2013.01); **B65B 43/50**

20 Claims, 34 Drawing Sheets



US 11,130,596 B2

Related U.S. Application Data					
		4,729,206	A *	3/1988	Francis B65B 7/2878 53/297
(60)	Provisional application No. 62/783,394, filed on Dec. 21, 2018, provisional application No. 62/662,918, filed on Apr. 26, 2018.	4,782,644	A	11/1988	Haarer
		5,918,765	A	7/1999	Blankenship
		6,044,886	A *	4/2000	Mueller A21C 15/00 156/354
(51)	Int. Cl.	7,032,359	B1 *	4/2006	Robert B65B 25/148 53/136.2
	<i>B65D 77/14</i> (2006.01)	7,918,334	B2 *	4/2011	Gaetano A23G 3/2046 198/867.12
	<i>B65G 47/86</i> (2006.01)	9,125,435	B1	9/2015	Sinclair, Jr.
	<i>B65G 47/88</i> (2006.01)	9,776,751	B2 *	10/2017	Lukes B65G 47/28
	<i>B65B 31/02</i> (2006.01)	10,856,574	B2	12/2020	Ghiotti
	<i>B65D 71/06</i> (2006.01)	10,946,987	B2	3/2021	Ghiotti
(56)	References Cited	2003/0185948	A1	10/2003	Garwood
	U.S. PATENT DOCUMENTS	2007/0000567	A1 *	1/2007	Marletto
		2008/0145489	A1 *	6/2008	Green
		2012/0230809	A1	9/2012	Bellante
					OTHER PUBLICATIONS
		3,028,029	A	4/1962	Morse
		3,092,944	A	6/1963	Wise
		3,591,041	A	7/1971	DiGrande et al.
		3,618,642	A	11/1971	Beaulieu
		4,002,005	A *	1/1977	Mueller B65B 9/02 53/442
		4,188,768	A *	2/1980	Getman A23G 9/288 426/282
		4,608,809	A *	9/1986	Francis B65B 7/2878 53/297
		4,691,500	A *	9/1987	Danforth B65B 7/2878 156/69
					Kynd Custom Packaging, https://kyndpackaging.com/pre-roll-packaging/ , 9 pages, USA.
					Custom Cones USA, https://customconesusa.com/pre-roll-machines/ , 5 pages, USA.
					Futurola, https://futurolausa.com/36-knoobox-accessories , 2 pages, USA.
					Ganjarunner, https://ganjarunner.comishop/medical-marijuana-products/pre-rolls/ganjagold-blue-tarantula/ , 7 pages, USA.
					* cited by examiner




FIG 1A




FIG 1B




FIG 2A

FIG 2C




FIG 2B




FIG 3A




FIG 3C




FIG 3B




FIG 3E




FIG 3D




FIG 3F




FIG 3G




FIG 4C




FIG 4B




FIG 4A




FIG 4D




FIG 4F




FIG 4E




FIG 5A




FIG 5C




FIG 5B




FIG 5D




FIG 5F




FIG 5E




FIG 5G




FIG 5I




FIG 5H




FIG 6A




FIG 6B




FIG 6C




FIG 6D




FIG 6E




FIG 6F




FIG 6G

FIG 6I





FIG 6H







FIG 6L






FIG 6M

FIG 6N






FIG 6P

FIG 6O




FIG 7B




FIG 7A




FIG 7C




FIG 7D




FIG 8




FIG 9




FIG 10

US 11,130,596 B2

1

FOLDED PACKAGE

INCORPORATION BY REFERENCE

This application claims priority to and incorporates by reference in their entirety and for all purposes U.S. Provisional Patent Application Ser. No. 62/662,918 filed on behalf of Mark W. Holderman and Gregory August Russell, U.S. Provisional Patent Application Ser. No. 62/783,394 filed on behalf of Mark W. Holderman and Gregory August Russell, and PCT/US19/26711 filed on behalf of Mark W. Holderman and Gregory August Russell.

BACKGROUND

Prior to the development of the present apparatus and system, paper cones were filled by hand. People would individually stuff product, such as leaves, into a single cone, and mechanically tamp down the leaves. Alternately, numerous cones could be placed in what is essentially a honeycomb structure with holes that accommodate the cones. Crumbled leaves were then scattered over the holes containing the cones and vibrations or mechanical tamping was used to pack the leaves into the cones.

Each of the foregoing resulted in inaccurate and non-uniformly filled cones. The mechanical tamping often left the leaves too compacted. Sometimes the leaves at the bottom of the cone would be packed too much, while the leaves toward the top of the cone would remain too loose. The mechanical pressure had a tendency to rip the paper cones. Simply relying on vibrations to fill the cones would often result in leaves that were too loose.

These problems were often compounded by the type of plant matter used. Specifically, for plant matter containing a relatively high oil content, the crumbled leaves tended to exhibit a sticky quality that resulted in clumping of the leaves together. The clumped leaves negatively affected the utility of the vibration method because the vibrations alone were not sufficient to break up the clumps. Similarly, the tamping method simply resulted in clumps that were more tightly packed together, exacerbating the problem. In both cases, the clumps tended to lodge in the narrow part of the cone creating air gaps or otherwise non-uniform packing of the plant material within the cone.

Non-uniform packing creates a number of problems. For example, it can affect the weight of the final product. When clumps get packed in with more loose plant matter, the density of the clumps can result in more than the desired amount of plant matter being packed into the cone. The clumps tend to burn at a different rate, disrupting the natural and correct burn rate of a correctly and uniformly packed cone. When clumps create air-gaps, the burn rate of the plant matter can be negatively affected because the lack of solid contact among the plant matter can result in an extinguishing of the plant matter. The density of the clumps can disrupt the flow of air through the plant matter, and act like a blockage in a straw.

Filling cones by hand, or with the honeycomb type packing device also necessitates closing each of the cones by hand. Using those methods, a person was required to manually manipulate each cone and fold the open end to seal in the plant material and prevent it from falling out. Often the cones would simply be closed by twisting the paper on top of the cone together to completely close and seal the top of the cone. That manual process is taxing on a person's hands and limits the number of cones that can be filled in a given amount of time. It also tends to result in non-uniform

2

folded/twisted closures as people tend to have different techniques for folding/twisting and dexterity becomes more limited as hands and fingers become more fatigued.

SUMMARY

The present system provides an apparatus that accurately and uniformly fills paper cones with loose particles and closes the cones to prevent the particles from escaping the cones. While embodiments may generally be described herein as filling the cones with crumbled plant matter, such as crumbled dried leaves, it should be understood that any loose particles that could fit within the cone could be used as a filling for the cone without departing from the general scope of the apparatus and system. For simplicity, all such loose particles will simply be referred to herein as "leaves," but the use of that term herein in no way limits the apparatus to only packaging organic plant matter. It should be understood that while "paper" is a common substance to be used for cones, that term is used generically herein for any relatively thin, flexible, flammable substrate and is not strictly limited to traditional paper. It should be understood that the term "cone" need not be a traditional cone with a point at one end, but may be of any generally cylindrical shape or shape having a greater length than width (or diameter, where the term "width" as it is used in describing the width of an object having a circular cross section is the diameter), though preferably the shape of a truncated traditional cone.

The present apparatus and system overcome the shortcomings of the previously described manual methods by ensuring that the leaves are uniformly and consistently packed into the cones. The process is automated, allowing for consistent packaging and uniformity in the final product. It expedites the overall process of packing the cones. The present apparatus and system includes a number of sub-components that individually perform packing functions. The sub-components each individually overcome different problems that occur when manually packaging leaves in cones. For example, an embodiment of the present apparatus and system includes a leaf hopper and trough conveyor. It precisely measures units of leaves for packaging, breaks up clumped leaves initially and prevents clumping of the leaves as the leaves are transferred through the apparatus. A conveyor, such as a carousel, manages the flow of cones into the system. It holds large quantities of cones and moves them into the precise position for packaging while preventing undesirable crimping and folding of the cone that could otherwise affect the quality of the finished, packed cone.

Another sub-component is the packing sub-assembly. It includes a hopper that feeds leaves into the cone. A combination of vibrations and successive applications of pulsed air may be used to ensure even distribution and uniform packing of leaves in the cone. A vacuum system is further connected to remove any stray leaves that failed to properly be packed into the cone and thereby prevents unnecessary buildup and waste of leaves.

A folder sub-component and injector sub-component (which in some embodiments are incorporated into a single sub-component while in other embodiments are arranged as separate sub-components) complete the packaging of the cone. The folder sub-component properly orients the cone. Folding fingers precisely bend a portion of the cone and a folding tip compresses the bent portion of the cone to close it. Depending on the product being packaged into the cones, it may be advantageous to inject a further substance, such as oil, into the packed cone. In some instances the oil may be derived from the same family of product that is being

US 11,130,596 B2

3

packed into the cone, such as an oil derived from the same plant family as the leaves that are used to fill the cone. In such instances, after compressing the cone with the folding tip, an injector needle penetrates the cone and is withdrawn, leaving a deposit of the further substance through the leaves in the cone as the needle is withdrawn. This creates a line, or core, of the further substance through the leaf filled cone.

In one embodiment, after completing the folding, and if desired injecting, steps, the packaged cone is transferred to a quality control station. The quality control station checks to ensure the packaged cone meet the necessary quality parameters, for example, weight, shape, and color. Passing cones are transferred to an appropriate receptacle, while failing cones are rejected. Injecting could also be accomplished separately and after inspection.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a perspective view of an embodiment of the apparatus and system depicting the relationship between various sub-systems of the apparatus.

FIG. 1B is a perspective view of an alternative embodiment of the apparatus and system depicting the relationship between the various sub-systems of the apparatus.

FIG. 2A is a perspective view of an embodiment of the carousel.

FIG. 2B is a close-up plan view of a portion of one embodiment of a plate of the carousel exhibiting a geometric hole.

FIG. 2C is a perspective view of an embodiment of a cone.

FIG. 3A is a perspective view of an embodiment of the carousel in relation to an embodiment of de-nesting fingers and an embodiment of a cone conveyor.

FIG. 3B is a close-up perspective view of an embodiment of de-nesting fingers in a closed position.

FIG. 3C is an exploded view of an embodiment of de-nesting fingers.

FIG. 3D is a side view of embodiments of a cone conveyor and dies.

FIG. 3E is a perspective view of embodiments of a cone conveyor and dies.

FIG. 3F is an exploded view of an embodiment of a die.

FIG. 3G is a perspective view of an embodiment of a die.

FIG. 4A is a side view of embodiments of a hopper and conveyor.

FIG. 4B is an alternative side view of embodiments of a hopper and conveyor.

FIG. 4C is a perspective view of embodiments of a hopper and conveyor.

FIG. 4D is a close-up side view of an embodiment of a hopper and conveyor depicting a portion of the hopper within the conveyor along with a damper plate within the conveyor.

FIG. 4E is a perspective view of an embodiment of a grinder hopper and wheel.

FIG. 4F is an alternative perspective view of an embodiment of a grinder hopper and wheel.

FIG. 5A is a perspective view of an embodiment of a packing station.

FIG. 5B is a perspective view of an embodiment of a packer head.

FIG. 5C is an alternative perspective view of an embodiment of a packer head.

FIG. 5D is an exploded view of an embodiment of a packer head.

4

FIG. 5E is a perspective view of an embodiment of a weigh station in a closed position.

FIG. 5F is an alternative perspective view of an embodiment of a weigh station.

FIG. 5G is an exploded perspective view of an embodiment of a cone support system.

FIG. 5H is a side view of an embodiment of a cone support system oriented in relation to an embodiment of a cone conveyor.

FIG. 5I is a perspective view of an embodiment of a cone support system oriented in relation to an embodiment of a cone conveyor.

FIG. 6A is a perspective view of an embodiment of a folder station.

FIG. 6B is an exploded view of an embodiment of folder fingers.

FIG. 6C is a partially exploded perspective view of an embodiment of a portion of a folder station including an injector needle.

FIG. 6D is a cross-sectional side view of an embodiment of a folder station including an injector needle with an unfolded cone.

FIG. 6E is a cross-sectional side view of an embodiment of a folder station including an injector needle with a partially folded cone.

FIG. 6F is a cross-sectional view of an embodiment of a folder station with injector needle inserted into a cone.

FIG. 6G is a cross-sectional view of an embodiment of a folder station with injector needle extracted from a cone and a cone having a fluid core.

FIG. 6H is a close-up plan view of an embodiment of folder fingers in a partially closed state.

FIG. 6I is a close-up plan view of an embodiment of folder fingers in a closed state.

FIG. 6J is a side view of an embodiment of folder fingers in an open state.

FIG. 6K is a plan view of an embodiment of folder fingers in an open state.

FIG. 6L is a perspective view of an embodiment of a folder tip with an axial pin.

FIG. 6M is a plan view of an embodiment of a folder tip with an axial pin.

FIG. 6N is a cross-sectional side view of an embodiment of a folder tip with an axial pin.

FIG. 6O is a perspective view of an embodiment of a cone folded by an embodiment of the folder tip with an axial pin.

FIG. 6P is a cross-sectional side view of a distal end of an embodiment of a filled cone with a fluid core folded by an embodiment of the folder tip with an axial pin.

FIG. 7A is a side view of an embodiment of a fluid injector station.

FIG. 7B is a perspective view of an embodiment of a fluid injector station.

FIG. 7C is a cross-sectional side view of an embodiment of a fluid injector station.

FIG. 7D is a perspective view of an embodiment of an injector station and gas purge packaging station.

FIG. 8 is a perspective view of an embodiment of a quality control station.

FIG. 9 is a flowchart describing the operation of an embodiment of the packaging assembly.

FIG. 10 is a schematic of an embodiment of a control system in connection with a plurality of actuators and sensors.

DETAILED DESCRIPTION OF EMBODIMENTS

Throughout the specification, wherever practicable, like structures will be identified by like reference numbers. In

US 11,130,596 B2

5

some figures, components, such as additional electrical connections and tubing (such as vacuum tubing and pneumatic tubing) have been omitted for clarity in the drawings. Additionally, in some figures repetitive structures, such as multiple actuators have been omitted. In such cases exemplary components are provided for explanatory purposes and it should be understood that other similar devices in the drawings may be provided with similar components. Unless expressly stated otherwise, the term “or” means “either or both” such that “A or B” includes A alone, B alone, and both A and B together.

FIG. 1A and FIG. 1B generally depict embodiments of a packaging assembly 100. Embodiments may include a carousel 200, a cone conveyor 300, a hopper assembly 400, a leaf conveyor 407, a grinder hopper 401, a packing station 500, a weigh station 510, a folder station 600, and a quality control station 800. Additionally, the packaging assembly may include a conveyor 806, and an injector station 700 (which may be integrated with the folder station or a separate station). The various components may be mounted to a table 101.

The packaging assembly is also equipped with a number of actuators. The actuators move the various components of the assembly into their proper positions. In one embodiment, the actuators are generally pneumatic actuators and electric motors, though it should be appreciated by one of ordinary skill in the art that any actuator could be used. By way of non-limiting example, continuous speed motors, variable speed motors, servo motors, hydraulics, or magnetic actuators could be used. By way of further example, an actuator could be in the form of a simple valve or switch that the control system operates to permit a hydraulic or pneumatic fluid to flow through the system and provide the force required by the system. A vacuum pump and vacuum tubing may also be utilized to control airflow in the system.

An electrical control system (one embodiment of which is described in further detail with respect to FIG. 10) is used to monitor and control the operation of the system and packaging assembly. The electrical control system may include dedicated circuits, programmable computer hardware, firmware, software, controllers, or a combination thereof. The control system coordinates the operation of the apparatus and system and particularly coordinates the actuators and the vacuum as well as utilizing sensor data, preset parameters stored in the control system, or a combination thereof. While it generally is advantageous to utilize a control system of a self-contained, locally oriented computer (with accompanying input and output devices such as a display, keyboard, mouse, touch screen, voice command control, etc.) to reduce latency in the feedback and command loop between the sensors, computer, and actuators, it is contemplated that parts of the control system could be organized in a distributed manner, with sub-control systems operating portions of the packaging system while networked with a main computer controller, or even that portions of the control system could be located off-site and connected over the internet.

In one embodiment, a computer monitors the sensors of the packaging assembly, and coordinates the operation of the actuators of the packaging assembly. Simultaneously, the computer records data respecting the operation of the packaging assembly. For example, the computer records the time each actuator is activated. The computer system may further compile the number of operations of each actuator to determine whether a completed product should have been created. For example, the computer identifies that the actuators of the carousel were activated, followed by the activation of the de-nesting fingers. A feedback sensor on the de-nesting

6

fingers informs the computer that a cone was successfully withdrawn from the carousel and the computer logs that data. The computer then records activation of the cone conveyor and the activation of a weigh station sensor and weigh station actuator (indicating that product has been fed to the cone). The computer system logs the activation of the packing rod actuator followed by the activation of folding finger actuators (indicating that the filled cone has been completed), the computer then logs the die actuator (releasing the filled cone) followed by sensor feedback from quality control sensors (such as recording the weight of the cone, an image of the cone, or a simple check that the cone is present). The computer then records whether the reject actuator was activated to determine whether the cone was accepted or rejected. The computer records the subsequent activation of the actuators of the fluid injecting station, including the operation of the fluid pumps to record whether the cone was filled with a fluid core, and how much fluid was deposited in the cone. Subsequent quality control data (and acceptance/rejection data) as described previously may be recorded. In some embodiments the fluid filling occurs prior to any quality control. By coordinating the recording of the data pertaining to the actuators and sensors, the computer system is able to track individual cones as they progress through the packaging system.

When a cone is expected, but not present, the computer may log the instance and generate an alert. For example, if all actuators and sensors are logged from the extraction of a cone from the carousel to the folding station, the computer expects that a filled cone will next be present in the quality control station. If the die actuator activates and no filled cone is sensed at the quality control station, the computer can generate an alert indicating that the expected filled cone is missing. In that way, the computer system can help prevent theft of completed cones.

Also, the data can be used to assess the operation of the packaging assembly. The preferred timing of the actuators is known and stored in the memory of the computer. As the computer gathers data, it compares the actual timing against the preset value for optimal timing. If the actual data is outside of a preferred range, the computer may adjust the actual timing of one or more of the actuators (for example, the computer may activate an actuator slightly earlier than previously to bring the actuator into the proper timing) or may generate an alert to have a technician reset the operation of the assembly (or actuator). The control system may be connected to the internet such that data regarding the operation of the actuators and sensors may also be transmitted to a remote computer for monitoring the operation of the assembly remotely. In one embodiment, when the computer compiles data regarding the coordinated activation of the actuators and sensors indicating that a cone has been filled and quality checked, the computer increments the number of cones filled (subtracting and logging the number of cones rejected). The computer system may then generate a report indicating the number of cones filled and accepted over a particular time period.

In general, the components are arranged to facilitate the movement of a cone through the packaging system. In one embodiment, the cone conveyor is adapted to move the cones from station to station to effectuate filling of the cones. For example, in the embodiment of FIG. 1A, when the conveyor is moved in the forward direction (which in FIG. 1A corresponds to the counterclockwise direction, though it should be understood that “forward” simply means a direction that moves a point on cone conveyor from a starting point successively past stations of the packaging apparatus

US 11,130,596 B2

7

before returning that point to the starting point), the cone conveyor moves a cone from the carousel to the packing station, then to the folding station, then to the quality control station before returning to the starting point of the carousel and receiving another cone.

FIG. 2A generally depicts an embodiment of the carousel 200. It includes at least one plate. It should be appreciated that a “plate” could be of any size and shape, and is not limited to a flat plate as shown in FIG. 2A. Rather, a flat, generally circular plate (as shown) can effectively and economically convey the cones in the present system. In the embodiment shown, the carousel includes three plates 210, 220, 230 arranged vertically along a support rod 240. The support rod is connected to a rod actuator 250. The rod actuator 250 rotates the support rod and thereby rotates the carousel including plates 210, 220, 230.

With reference to FIGS. 2A and 2B, each of the plates includes a series of holes located circumferentially along an outer perimeter (see generally, 280) of the plate. For example, in FIG. 2B, plate 230 includes holes 231, 232, 233, 234, 235, 236, 237, and 238. Preferably, the holes of the upper two plates, 210 and 220, have diameters that are the size of or slightly larger than the largest diameter of the cones 1100. Thus, the cones may pass freely through the holes of those two plates. In one embodiment, the holes of plate 230 have a diameter that is less than the largest diameter of the cones, or have a geometric shape that results in frictional engagement of a cone placed in the hole. In one embodiment, the holes of plate 220 each include a hole actuator and a hole clamp (for explanatory purposes, only one hole actuator and hole clamp is depicted). As an example, FIG. 2A depicts hole actuator 260 and hole clamp 270. The hole actuator actuates the hole clamp to apply and release pressure on the stack of cones such that when pressure is applied, the cones are prevented from passing through the associated hole on plate 220. That assists in relieving the pressure on the cone that is frictionally engaged with the geometric hole 236 and prevents the weight of the cone stack 1100a from prematurely pushing cones through the geometric hole. When pressure is released, the cones may pass through the hole associated with the actuator and clamp on plate 220 under the weight of the stack of cones 1100a. In one embodiment the actuator 260 includes a piston 261 that connects to a movable clamp block 271. A fixed clamp block 272 is fixed to plate 220. The actuator 260 actuates the piston to slide the movable clamp block 271 toward and away from the fixed clamp block 272 to apply or release pressure on the cone stack 1100a. Thus, the actuator moves the clamp to create and alleviate a restriction at the associated hole so as to prevent or allow cones to pass through the hole. It should be appreciated that alternative clamps could be used such as a constricting (or sphincter) clamp that encircles the cones such that the actuator constricts and releases the clamp to apply and release pressure on the cone stack.

Respecting the cones, cone 1100 of FIG. 2C is an example of a cone that may be packed using the present system. The cones are stacked in a nested fashion in the carousel (see, generally, 1100a). The cones exhibit a proximal end 1101 and a distal end 1102 that are located opposite one another and joined by a middle section. The cones are hollow such that air may enter the distal end, be drawn through the cone, and exit the proximal end. Preferably, the distal end exhibits a diameter that is larger than the diameter of proximal end.

Preferably, each of the holes 231, 232, 233, 234, 235, 236, 237, and 238 on the bottom plate 230 is not circular. Rather, as shown in FIG. 2B which depicts an exemplary hole 236

8

in an expanded view, the wall 239 of each hole each may include a geometric shape. As used herein, “geometric” means that the shape is not a circle. Preferably, the geometric shape is an eight pointed star. The use of a hole with a wall having a geometric shape reduces the size of the hole so that it is smaller than the largest circumference of the cone. Thus, a cone will not pass through the hole 236 under its own weight, but instead must be forced through. The preferred size of the geometric shape is only slightly smaller than the greatest circumference of the cone so that as the cone is forced through the hole, the paper cone resiliently deforms and the geometric shape prevents plastic deformation of the cone, such as a crease in the cone. In one embodiment, the geometric shape is formed in the plate by cutting a hole that has a geometric shape into the plate. Alternately, a hole of any shape, including circular, could be cut into the plate and that hole could be filled with a material, such as a molded resin, plastic, or rubber, that surrounds the wall of the hole and that has an interior hole that is a geometric shape.

In one embodiment, the cone is extracted from the carousel 200 by being pulled down through the geometric hole. An actuator activates, for example, a clamp or a suction cup to temporarily attach to the cone and pull the cone from the carousel 200. It should be appreciated that an alternative carousel in the form of a flexible conveyor, in place of rigid plates, could be utilized to move stacks of cones into position proximal to the cone conveyor so as to enable the transfer of cones from the carousel to the cone conveyor. It should be appreciated that while one embodiment uses three plates, an alternate embodiment could use more plates and more actuators to relieve the weight of taller stacks of cones. Alternately, fewer plates could be used, and depending on the weight of the stack of cones, a simplified embodiment could eliminate the use of actuators to relieve the weight of the stacks of cones.

FIG. 3A depicts an embodiment of the system including the positioning of the carousel 200, the cone conveyor 300, and de-nesting assembly 360. With reference to FIG. 3B, in one embodiment, the cone may be grasped by de-nesting fingers 361 and 362. One or more of the fingers are moved by a de-nesting actuator 363 to open and close the fingers and are also moved by a vertical actuator 364 to adjust the vertical position of the de-nesting fingers with respect to the cone conveyor 300.

FIG. 3B is a depiction of an embodiment of the de-nesting assembly. De-nesting finger 361 has a notch 365 cut in a distal end of the finger 361. In one embodiment, the notch is V-shaped. De-nesting finger 362 has an approximately vertical plate 366 extending from a distal end of the finger 362. The vertical plate may be flat, curved to match the curve of the paper cone, or angular to approximate a curve. In one embodiment, the vertical plate is T-shaped. The notch 365 and vertical plate 366 are calibrated such that the when the de-nesting fingers come together, the notch and vertical plate sufficiently contact the cone so as to frictionally engage the cone without causing plastic deformation of the cone. The de-nesting actuator 363 brings the de-nesting fingers together to engage the cone, and the vertical actuator 364 moves the de-nesting fingers vertically to extract the cone from the carousel 200. It should be appreciated that while two actuators may be used, a single multi-axis actuator could also be used. The T-shape of the plate on de-nesting finger 362 helps provide additional frictional surface area to help engage the cone and prevent plastic deformation. In some embodiments, the de-nesting fingers may be coated with a frictional material, such as soft rubber or plastic, to increase the friction between the de-nesting fingers and the cone. In

US 11,130,596 B2

9

an alternate embodiment, the de-nesting fingers may be replaced with a de-nesting suction cup such that the suction cup attaches to the cone by vacuum, the de-nesting assembly pulls the cone down, and then the vacuum is released detaching the suction cup from the de-nested cone.

In one embodiment, vertical actuator **364** moves the de-nesting fingers **361**, **362** to extract one cone while the packaging assembly simultaneously activates hole actuator **260** on the second plate to open and allow the stack of cones to move vertically. Once the stack moves sufficiently vertically downward (which can be determined, for example, based on timing or sensor feedback), the hole actuator **260** engages the next cone to support the weight of the stack of cones, and the bottom cone sufficiently engages (such as by friction) the geometric hole **236** to hold the remaining cones.

Thus, as one cone is removed from the bottom of the stack of cones **1100a**, the hole actuator **260** temporarily releases pressure on the stack of cones and allows the stack to lower by one cone. The hole actuator **260** then reapplies pressure to the stack to prevent more than one cone from exiting through the hole in the lower plate **230**. Once all of the cones in one stack are pulled through the hole in the lower plate **230**, the rod actuator **250** rotates the plates such that the next stack of cones (not shown) is in position to supply additional cones. In one embodiment, an empty sensor **367** identifies that a cone was not grasped by the de-nesting fingers as the de-nesting fingers come together completely, thus tripping the sensor. Upon receiving a signal from the empty sensor **367**, the control system may attempt to grasp a cone again. After one or more failed attempts, the control system may determine that the stack of cones **1100a** is depleted and send a signal to turn the carousel **200** and orient a new stack of cones over the de-nesting fingers before attempting to again grasp a cone.

The cones are extracted from the cone stack and deposited on the cone conveyor **300**. As shown in FIGS. 3D and 3E, the cone conveyor includes a die-plate **301**, dies **310**, **320**, **330**, **340** (though it should be appreciated that while four dies are shown, more or less dies could be utilized), a support shaft **302**, and a cone conveyor actuator **303**. The die-plate **301** is mounted to support shaft **302**. The cone conveyor actuator **303** rotates the support shaft and thereby rotates the die-plate **301** to convey the dies (and any cone a die contains) through the packaging assembly. It should be understood that the cone conveyor actuator could be adapted to drive the cone conveyor directly (such as by mounting directly to the die-plate and thereby rotate the die-plate directly). In such an embodiment, the support shaft **302** may be unnecessary. However, in one embodiment, the support shaft may be used to provide separation between the die plate **301** and a mounting surface (such as a bench or table) (see, for example, FIG. 1, table **101**). It should be appreciated that a larger cone conveyor with more dies could be utilized, and even a flexible conveyor with many dies.

In one embodiment, the cone conveyor **300** may include multiple dies, and preferably includes four dies **310**, **320**, **330**, and **340**. The dies may hold a cone to be filled and allows a filled cone to be extracted from the die. For explanatory purposes, an embodiment of a die is shown in FIGS. 3F and 3G. The die may be made of two clamping segments **311** and **312** (though more complex dies made of more clamping segments or an alternative structure could be used). Clamping segment **311** has a contact surface **311a** and a groove **311b** while clamping segment **312** has a contact surface **312a** and groove **312b**. When brought together, contact surface **311a** mates with contact surface **312a**, and the grooves **311b** and **312b** of the clamping segments define

10

a cavity (see, generally **313**) having a distal end **314** and a proximal end **315** that traverses the vertical thickness of the clamping segments. In some embodiments the vertical thickness of each clamping segment may be the same, but in other embodiments the vertical thickness of one clamping segment (for example **311**) may be different than the vertical thickness of the other clamping segment. Preferably, the cavity **313** exhibits the shape of a truncated cone such that the diameter of the cavity is larger at the distal end **314** and tapers toward the proximal end **315**. A die actuator **350** moves one or more of the segments to open and close the clamping segments **311**, **312**, and thereby open and close cone shape cavity **313** allowing a filled cone to be extracted from the die. In operation, de-nesting assembly **360** deposits a cone into cavity **313** of the die **320** and the cone is held by the die. The cone is then filled, and die actuator **350** may then separate the clamping segments **311** and **312** and the cone may pass through the die. That also may prevent the cone from undergoing plastic deformation as could occur if the cone were forcibly removed from the die, such as could happen from gripping the cone.

With respect to filling the cone, after the cone is deposited in the die, the cone conveyor rotates and positions the cone beneath a packing station **500** which, in one embodiment is associated with a hopper station **400** (see FIGS. 1A and 1B). In one embodiment, the hopper station includes a conveyor **407**. With reference to FIGS. 4A-4D, leaves (not shown) are fed into hopper **401b**. In one embodiment, as shown in FIG. 4C, the hopper comprises a container that is generally a three-dimensional rectangle with four sides. It should be appreciated that the hopper could be a different shape, such as tubular with uniform, seamless sides. The hopper includes a hopper inlet **402** at the top, through which leaves may be supplied, and a hopper outlet **403** at the base to allow for leaves to exit the hopper. At the base of the hopper is a damper plate **404** that closes the base of the hopper outlet **403** and prevents leaves from exiting. The hopper is preferably mounted proximally to the damper such that when the packaging apparatus is not in operation, there is a gap **405** between the hopper outlet **403** and the damper plate **404**. The hopper or damper plate or both may be adjustable to increase or decrease the gap between them depending on the size of the leaves. In one embodiment, the damper plate is connected to the inside of the conveyor **407** and is actuated by leaf conveyor actuator **408** which moves with the conveyor and damper plate relative to the hopper and thereby meters out leaves from the base of the hopper. Alternatively, the damper plate could be mounted directly to an actuator whereby that actuator vibrates the damper plate relative to the hopper and thereby meters out leaves from the base of the hopper. It should be appreciated that the hopper could alternatively or additionally be connected to an actuator to effectuate movement of the position of the hopper relative to the damper. In one embodiment, the damper plate is mounted to the conveyor **407** which is in-turn connected to a leaf conveyor actuator **408** such that one actuator may be used to vibrate both the damper plate **404** and the conveyor **407** simultaneously. In one embodiment, the conveyor **407** is mounted to a base **409** by one or more resilient mountings. For example, resilient mounting springs **410**. The resilient material assists in effectuating consistent vibration between the conveyor and hopper. As noted, to assist in the flow of leaves out of the hopper, the damper plate or hopper may be adjustable such that the static distance of the gap between the damper plate and the hopper is variable. For products

US 11,130,596 B2

11

that have a very fine texture, that static distance may be set very small, but it may be increased when large grain products are being fed.

In one embodiment, the conveyor is substantially V-shaped and forms a channel that moves leaves along the length of the conveyor from a deposit end **412**, where leaves are deposited by the hopper to an output end **413**, where the leaves are output to the packing station. In one embodiment, the hopper **401** exhibits a tapering shape. For example, where a box-shaped hopper is used, the hopper outlet **403** at the base of the hopper may be approximately 3 inches square while the hopper inlet **402** at the top of the hopper may be approximately 2.5 inches square. That configuration is advantageous because it restricts the incoming flow of leaves and allows the leaves to move from a lower volume space at the top of the hopper to a larger volume space at the base of the hopper. That helps prevent clumping of the leaves in the hopper.

The hopper deposits leaves onto the leaf conveyor **407**. In one embodiment the leaf conveyor is constructed of a uniform piece of sheet metal that is bent into a V-shape. While it is conceivable that other materials could be used, the use of sheet metal helps prevent static buildup and thereby assists in consistent conveying of leaves. Forming the conveyor of a uniform sheet of material eliminates seams where leaves could otherwise be caught. The V-shape helps create a uniform line of leaves and thereby maintains a consistent flow of leaves along the conveyor. That assists in reliable filling of the cones later in the process. Additionally, the sides of the conveyor may be wider apart at the deposit end and then narrow as the conveyor approaches the output end. That allows leaves to easily be caught by the conveyor as they exit the hopper at the deposit end and form into a controlled line at the output end of the conveyor.

Additionally, the conveyor is slightly upwardly angled in the conveying direction. That is, as leaves move along the conveyor away from the hopper, the leaves rise. A leaf conveyor actuator **408** is connected to the conveyor. The actuator vibrates the conveyor to cause leaves to move along the length of the conveyor. The combination of the vibrations and the rise in the conveyor assists in creating a uniform line of leaves within the conveyor which leads to more consistent depositing of leaves into the cones.

In one embodiment, as shown in FIG. **4D**, a sensor **415** monitors the level of the leaves moving along the conveyor and provides feedback to the control system (for example via wire relay or wireless communication) to activate an adjustment actuator **416** that adjusts the positioning of the hopper **401** with respect to the damper plate **404** thereby adjusting the gap **405** between the hopper and the plate to permit more or less leaves to exit the hopper. It should be appreciated that the adjustment actuator could adjust the position of the hopper (while the damper plate **404** remains fixed with respect to the conveyor), or the adjustment actuator could adjust the position of the damper plate **404** (while the position of the hopper remains fixed). The sensor may be a photoreceptor that captures data relating to the height of the leaves moving along the conveyor. The sensor relays the data to the control system over a sampling period, for example every 1 second, and the control system determines whether the height of the leaves is within an acceptable range. If it is out of range, for example too high (indicating too many leaves are exiting the hopper), the control system may send a signal to an adjustment actuator causing the adjustment actuator to move and adjust the respective positioning of the hopper **401** and damper plate **404**. In one embodiment, the actuator is a linear actuator that

12

moves to slide the hopper closer or further away from the plate. While the increments of movement may vary, for general leaf based products, it has been found that movement of the relative position of the hopper to the damper in 0.1 mm increments tends to result in the optimal adjustment of product flow.

In an alternate embodiment, an alternative hopper may be used in addition to the conveyor **407** or even in place of the conveyor. As shown in FIGS. **4E** and **4F**, a grinder hopper assembly **450** may be utilized. The grinder hopper assembly **450** includes a hopper **401a** having a hopper inlet **402** and a hopper outlet **403**. At the outlet of the hopper is a wheel **451** that is operated by a wheel actuator **452**. The wheel may include a textured surface so as to function as a grinding wheel. In one embodiment, the hopper funnels toward the hopper outlet **403**, and the outlet is approximately the same width as the wheel **451**. A portion of the wheel fits within the hopper outlet so as to substantially block the flow of leaves out of the hopper while leaving a gap between a surface of the wheel and a portion of the hopper. The control system sends a signal to the wheel actuator to drive the wheel. When leaves are in the hopper, as the wheel spins it draws leaves through the gap between the wheel and the hopper. When a textured wheel is used, the spinning of the textured wheel may grind the leaves as the leaves are forced between the surface of the wheel and the hopper at the hopper outlet. As the leaves exit the outlet, they may be deposited into the conveyor **407**, or alternatively deposited directly into a weigh station.

With reference to FIGS. **1A-1B** and FIGS. **5A-5F**, the packing station **500** is associated with a weigh station **510**, a chute **520** with chute inlet **521**, a chute exhaust port **530**, a packer head **570**, an outlet funnel **550** with an exit hole **551**, and a packing rod **541**. In one embodiment, the packing station includes an inlet funnel **501**. The conveyor or grinder hopper deposits leaves into the weigh station **510**. The weigh station includes a sensor for determining the proper amount of leaves. Any number of sensors could be used, such as optical, sonic, and contact sensors. It should be appreciated that the weigh station need not actually weigh the leaves. In one embodiment, the sensor is a contact sensor that senses the weight of the leaves. As shown in FIGS. **5E** and **5F**, one or more sensors **511** are associated with the outlet doors **512**, **513** at the bottom of the weigh station (though a single outlet door or multiple outlet doors could be utilized). The outlet doors are configured to open and close to allow leaves to build up in the weigh station and then be deposited in the packing station (such as through the chute **520** through chute inlet **521**). In one embodiment, one or more sensors **511** send signals to the control station as the leaves are deposited in the weigh station. In an embodiment utilizing the grinder hopper assembly **450**, leaves may be deposited directly from the hopper outlet **403** into the weigh station, the weigh station may send signals to the control station indicating the weight of the leaves, and as the weight increases (or at preset weight thresholds stored in the control system) the control system controls wheel actuator **452** to vary the speed of the wheel. For example, as the weight of leaves increases, the control system slows the speed of the wheel to more accurately deposit smaller amounts of leaves to hit a target weight (which may be a preset value stored in the control system). When the proper amount of leaves fill the weigh station, and the control system signals one or more weigh station actuators **514** to open the outlet doors of the weigh station and release the leaves into chute **520**. The control system may then increase the speed of the wheel actuator (and wheel) to initially more rapidly fill the weigh station.

US 11,130,596 B2

13

One or more actuators open outlet doors **512**, **513**. The leaves fall down the chute **520** and into the packer head **570** where they are deposited into an outlet funnel **550**. The packer head is essentially a cavity that contains leaves from the chute in preparation for filling a cone (though it should be understood that the chute and packer head could be formed together as a unitary structure). In one embodiment, see for example FIG. 1B, the hopper outlet **403** and a portion of the wheel **451** nest inside the weigh station **510** (see nesting cavity **515** in FIG. 5E) so as to limit the possibility of leaves errantly exiting the weigh station and preventing unwanted debris from entering the weigh station.

The chute, packer head, and outlet funnel may be formed separately and connected together (such as by bolts or welding) or may be formed as an integral unit, or a combination thereof. In one embodiment, the chute, packer head, and outlet funnel are sealed together (or formed together) to prevent leaves from spilling out. The packer head and outlet funnel may also be connected to an actuator that moves the packer head and outlet funnel up and down. In operation, the packer head begins in a raised position, a die (for example, **310**) holding a cone is moved beneath the packer head, the packer head is then lowered onto the die. In some cases, the top of the cone may protrude from the top of the die. By moving the packer head, the die and cone may be moved into position and the packer head can also move into position and if necessary press the cone into the die all without risk that the cone will be damaged.

In one embodiment, the packer head **570** and outlet funnel **550** are lowered onto the die to engage the top surface of the die such that leaves are prevented from traversing the junction between the bottom of the outlet funnel and the top of the die. In one embodiment, a cone support system **560** (see FIGS. 5G-5I, and FIG. 6D). In one embodiment, the cone support system includes a cone support **561** that is connected to an support actuator **562**. The support actuator **562** may further be connected to a mounting bracket **563** and table mount **564** to fix the cone support system to table **101**. The support actuator **562** lifts the cone support **561** such that it may be moved to engage and disengage the proximal end of a cone that is within a die on the cone conveyor. In one embodiment, two cone support systems are provided, such as in FIG. 5H with, for example, cone support system **560a** being associated with the packing station **500** while cone support system **560b** is associated with folding station **600**.

In one embodiment, the cone support **561** is cup shaped with a cone bottom surface **565** at the base, a raised side wall, a suction rim **567**, and an exhaust port **568**. The cone support may also include a grate **569** such that when the cone support is lifted to engage with a proximal end of a cone, the grate separates the proximal end of the cone from the bottom surface **565**. When the die holding a cone is positioned under the packer head **570**, for example, the support actuator **562** moves the cone support **561** such that the contact surface **565** (or grate **569**) contacts the proximal end of the cone and adjusts the height of the cone within the die. In one embodiment, a sensor, such as a pressure sensor, is used to determine if the cone is at the proper height by registering resistance of the cone due to the distal end of the cone pressing against the funnel **550**. In another embodiment, the height of the cone is a preset value, and the cone support moves to a preset height beneath the packer head **570** to lift the cone to the proper height. The suction rim **567** contacts the bottom of the die holding the cone. A vacuum tube may be connected to the exhaust port **568**. With the rim **567** contacting the die, the vacuum may create a suction within the cone support **561** and, with the grate **569** lifting

14

the proximal end of the cone, the vacuum may draw air through the cone to assist with packing of leaves within the cone. The vacuum may also collect leaves that may fail to properly enter the cone or that completely pass through the cone.

The packer head is essentially an enclosed block (or container) that prevents leaves from escaping the funnel. Referring to FIGS. 5C and 5D, the packer head also helps guide the packing rod **541**. The packing rod is connected to a packing rod actuator **542** that moves the packing rod **541** within the packer head **570**. Preferably, the packing rod is hollow and connected to a pneumatic system that provides pressurized gas through the packing rod. The packer head **570** may also include an exhaust port **531**. Chute exhaust port **530** and exhaust port **531** may be connected to a vacuum system that may selectively turn on and off to clear the chute and packer head of leaves and keep the packing station free from a buildup of leaves.

In one embodiment, as leaves fall through the funnel **550** and out the exit hole **551** in the bottom of the funnel, the leaves are deposited into the cone and a burst of pressurized gas is applied to pack the leaves into the cone. The exit hole may be approximately the same size as the size of the distal end of the cone. Also in one embodiment, the hollow packing rod may be set to a static height, and the pressurized burst function operates the same. The packing rod may be set in a down position such that it closes the hole in the bottom of the packer head. For example, the packing rod has an external circumference that is approximately equal to the circumference of the exit hole **551** such that the packing rod may extend into the exit hole and substantially plug the exit hole. The actuator may slide the packing rod within the packer head and into and out of the exit hole to selectively plug and unplug the exit hole.

Leaves fall into the packer head and the packing rod in the down position prevents the leaves from falling out early. Then a packing rod actuator **542** separates the packing rod **541** from the exit hole **551** in the bottom of the funnel **550**. Leaves fall past the tip **540** of the packing rod **541** and through the exit hole **551** into the cone. The tip may be hollow and communicate with the hollow packing rod to allow pressurized gas to flow through the packing rod **541** and tip **540**. While the tip may be conical, alternative tips, such as flat, or rounded tips may be used. Successive pressurized bursts of gas are applied and, after each burst additional leaves are permitted to fall past the tip of packing rod such that the pressurized burst pushed the leaves into the cone. The packing rod may be raised and lowered successively such that, when raised, some leaves to enter the cone, then the rod is lowered to stop the flow of leaves while a burst of gas is applied, then the packing rod is raised and the process is repeated.

In one embodiment, the packing rod actuator **542** and packing rod **541** perform that process at least five times while the cone is being filled with leaves. In one embodiment, the pressure of one or more of the bursts of pressurized gas may be varied. For example, the first burst of pressurized gas may be applied at 60 psi, the second at 60 psi, the third at 45 psi, the fourth at 30 psi and the fifth at 30 psi or less. For cones that are approximately 4 cm to 6 cm long, it was found that the preferable range of bursts is between 10 and 15 when utilizing sticky leaves, and optimally 12 bursts, varying the pressure between 60 psi and 30 psi over the course of the application of bursts. Varying the pressure ensures that the leaves are uniformly packed within the cone. It also helps break apart any clumps of leaves that may have

US 11,130,596 B2

15

persisted from the conveying and weighing process. That too assists in ensuring that the leaves are uniformly packed in the cone.

In embodiments utilizing air burst, the bottom portion of the packing head funnel may be pressed into the top surface of the die so as to create a seal between the packer head and the die. In one embodiment, either the die top or the packer head bottom is equipped with a gasket to facilitate the seal. In operation, the packing rod is inserted into the exit hole of the funnel and may seal the exit hole both to prevent additional leaves from falling through the exit hole and into the cone, and to prevent leaves within the cone from blowing back up through the exit hole when a burst of gas is applied to the cone. In one embodiment, the exterior surface of the packing rod may be resilient and permit elastic deformation of the exterior of the packing rod when inserted through the exit hole to facilitate a seal. In one embodiment the material forming the exit hole may permit elastic deformation of the exit hole when the packing rod is inserted into the exit hole.

After the cone is packed at the packing station, the cone may be moved to the folder station **600**. With reference to FIGS. **6A-6P**, the cone conveyor **300** rotates and thereby moves a die from the packing station **500** to the folder station **600**. The folder station includes a housing **601** that accommodates a folding rod **602**. In one embodiment, the folding rod **602** is hollow and it guides an inner tube (or rod) **603** arranged within folding rod **602**. A folder tip **604** is affixed to (or integrated with) a distal end of the folding rod **602**, while a proximal end of the folding rod **602** is associated with a folding rod actuator **610**. In one embodiment, an injector needle **605** may be arranged coaxially with the folder tip **604** such that it may extend and retract from the folder tip **604**. In one embodiment, the inner tube **603** is connected at a distal end to the injector needle **605** (or the distal end of the inner tube may be integrated with the injector needle) and the proximal end is connected to a fluid transfer block **606** which is in turn connected to a fluid reservoir (not shown). The fluid transfer block **606** is connected to the injector needle **605** by an inner tube **603** and may include a fluid hole **607** that communicates with a fluid pathway (not shown) so as to allow fluid to flow from the fluid pathway into the fluid transfer block (and hence into the inner tube and injector needle) when the pathway and fluid hole are aligned, but also allow the fluid transfer block to slide within the housing. The fluid transfer block **606** may be located within the housing and include an actuator (not shown) that pumps fluid from the fluid reservoir through the inner tube **603** and out the needle **605**, and may also extend and retract the needle **605** (alternatively an additional actuator could be used to extend and retract the needle). For example, a pneumatic piston may be activated to apply pressure to the fluid transfer block and thereby force the fluid transfer block to pump fluid through the needle. That allows a variable pressure to be applied to the fluid transfer block, and by extension the fluid may be readily pumped out of the needle at a variable pressure.

The folder station **600** may further include a folding block **620**. In one embodiment, as shown in FIGS. **6A-6B**, the folding block includes four support structures **621**, **622**, **623**, and **624** each associated with a folding finger actuator **625**, **626**, **627**, and **628**, respectively, but it is conceivable that more or less support structures could be used. Each support structure is connected to (or integrated with) a folding finger **631**, **632**, **633**, and **634**. The connection could be accomplished through fasteners, such as screws or rivets, or the connection could be made by welding. Alternately the support structure and finger could be integrally formed such

16

that the support structure and finger are connected into single unitary piece. The support structures surround the folding block **620** having a cavity **629** extending vertically through it such that the cavity accommodates the folding tip and folding rod.

In one embodiment, the support structures are mounted to the folding block by one or more guide posts. In one embodiment, each support structure is mounted using two guide posts. For example, support structure **623** is mounted by guide posts **635** and **636**. The folding finger actuators **625**, **626**, **627**, and **628** move the support structures and fingers along the guide posts. It is conceivable that the guide posts could be eliminated and the actuators could be solely responsible for guiding the support structures.

In one embodiment, each folding finger has a distal edge with a recess formed in the distal edge. For example, folding finger **633** includes recess **637**. When the folding finger actuators move the support structures close to the folding block **620**, the folding fingers are moved closer to one another and the recess of each finger engage the top portion of the cone and cause the top of the cone to deform. That pre-folds the distal end of the cone. Preferably, the fingers are offset such that they slide over one another such that the recesses of opposing fingers (i.e. fingers **633** and **631**) are aligned when the fingers come together. One or more of the folding finger actuators may be actuated to move the folding fingers together and apart from one another. In one embodiment, the support structures are of approximately the same size and the guide posts are offset to ensure proper offset of the fingers. However, it is conceivable that the support structures could be made of different sizes or the mounting location could be altered to ensure the proper offset.

In one embodiment, only two folding fingers are utilized. With reference to FIGS. **6I-6J**, one embodiment includes folding block **620**, support structures **641**, **651**, folding fingers **642**, **652**, and folding finger actuators **643**, **653**. The folding fingers each include a recess **644**, **654**. In a further embodiment, recesses **644** and **654** are substantially V-shaped. For example, the recess **644** has a first side wall **660** and a second side wall **661** that converge at a vertex **662**. In one embodiment, rather than the sidewalls converging at a sharp, angular vertex to form the V, the walls converge at a concavity, such that the walls of recess **654** converge at concavity **655**, and the walls of recess **644** converge at concavity **645**. Preferably, each concavity is semicircular. The concavity ensures that when finger **642** and finger **652** come together (for example finger **642** is positioned to slide over finger **652** such that recess **644** partially eclipses recess **654**) a fold hole **663** remains between finger **642** and finger **652**. The fold hole **663** may accommodate a portion of the cone. Preferably, the hole is approximately 0.125 inches in diameter. The combination of the V-shaped recesses and the hole ensures that each cone pre-folds together in substantially the same manner. The preferred diameter of the hole keeps the pre-folded cone packed tightly together and enhances the uniformity of the button fold made by the folding tip.

With reference to FIGS. **6D-6G**, (which depict an embodiment of the folding station executing an example of a folding process and fluid injecting process) in one embodiment, a die **310**, containing filled cone **1120** is moved below the folding station **600**. In one embodiment, a cone support **561** supports the proximal end of filled cone **1120**. The cone support may be integrated with or connected to support actuator **562** that retracts when the cone conveyor **300** is rotating, and raises to contact (and in some embodiments lift) the filled cone **1120** when the cone conveyor is station-

US 11,130,596 B2

17

ary. The lifting and retracting of the filled cone 1120 can assist in ensuring that the distal end of the cone 1102 protrudes from the die 310 for proper folding, but allows the distal end of the cone to be below the folding fingers when the cone conveyor is rotating. In one embodiment, the cone support may attach to the cone (such as through suction or mechanical clamping). Folding finger actuators 643, 653 push the support structures toward the folding block 620 and the recess of each finger engage the distal end of the filled cone 1120 and cause the distal end of the cone to deform (see generally 690) and pre-fold the cone, folding rod actuator 610 causes the folding tip 604 to contact the pre-folded top of the cone as shown in FIG. 6E. In one embodiment the top of the cone is partially drawn down through the recesses of the fingers as the fingers close and deform the top of the cone. For example, the cone support attaches to the proximal end of the cone by vacuum, and the support actuator 562 retracts to draw the cone down. Drawing the cone through the fingers creases the paper to enhance the pre-fold of the top of the cone. The folder tip 604 is lowered onto the pre-folded cone. The fingers are retracted as the folding tip is pressed into the distal end of the cone. That presses the filled cone 1120 into the die 310 and completes the fold. In one embodiment, the pressure of the folding tip on the cone creates a button fold.

With reference to FIGS. 6I, and 6L-6P, there is depicted an embodiment of a folder tip 670 and a both a perspective view of a filled, folded cone and a cross-sectional view of a distal end of a filled, folded cone 1120. In one embodiment, the fold hole 663 is approximately the same shape and size as an axial pin 671 of a folding tip 670, such that the fingers 652, 642 may come together and press the paper of the cone against the axial pin 671. As the folding tip 670 presses into the distal end of the filled cone 1120, the axial pin 671 prevents the cone from fully enclosing the distal end, and when the folding tip is retracted, an access hole 1122 is formed in the folded paper 1121 of the filled cone 1120.

In one embodiment, the folding tip 670 includes and exterior circumferential surface 672, an interior circumferential surface 673, an axial pin 671, and a contact edge 674 as shown in FIGS. 6L-6N. Preferably the cross-section of the folding tip is circular, and preferably the diameter of the contact edge 674 is less than the largest diameter of the distal end of filled cone 1120. The exterior circumferential surface 672 of the folding tip 670 may be conical such that the angle α mates against the angle of the surface 316 of cavity 313 of a die (for example die 310). The interior surface may also be conical. Preferably, the angle β of the interior surface is between 80° and 85°. The interior circumferential surface terminates at the axial pin and contact edge, respectively. During the folding process, the folding tip may be placed at the distal end of the filled cone 1120 such that the axial pin 671 is below the rim 1103 of the distal end 1102 of filled cone 1120. As the fingers 642 and 652 converge, the axial pin prevents the fingers from completely collapsing the paper of the cone, and the paper of the cone is pressed against the axial pin. The folding tip 670 is pressed toward the filled cone 1120 such that the paper of the distal end of the cone slides up the axial pin and is bounded by the interior circumferential surface 673. The contact edge 674 presses the paper of the cone into the leaves within the cone, crimping the paper of the cone in on itself (see generally, fold lines 1130 of the folded portion of the cone (1121) and into the cone while the axial pin prevents the paper of the cone from completely covering the leaves. In this way, a portion of the paper of the cone is pushed into the interior of the cone, while a portion of the paper cone protrudes beyond

18

the level of the leaves 1140 (and any fluid 1124 where the filled cone is injected with fluid) creating a circumferential lip 1123 around the cone. Also in this way, the end of the cone is folded to prevent the escape of leaves while leaving a small hole 1122 in the end of the cone. Thus, as shown in FIGS. 6O-6P the filled cone 1120 has a proximal end 1101 (mouth) and a distal end 1102 (tip), a circumferential lip of paper 1123, folded paper 1121 inside the circumferential lip, and an access hole 1122, approximately in the center of the folded paper 1121 such that the rim 1103 of the filled cone 1120 is folded down and in toward the center of the diameter of the cone.

In one embodiment, the length of an unfolded cone is between approximately 4 inches and 4.5 inches in length. It was found that folding the distal end of the cone such that the folded portion pressed and contacted the leaves inside the cone was better suited to ensuring that leaves within the cone did not freely pour out of the cone when the cone was inverted (particularly in folded cones having an access hole 1122) and it improved lighting the distal end of the cone as opposed to leaving an air gap between the leaves in the cone and the folded paper. Additionally, it was found that folding the cone such that the circumferential lip 1123 extended between approximately 2 mm and 5 mm produced optimal results while maximizing the interior volume of the cone that could be filled with leaves.

A number of benefits were found when folding the tip of the cone to provide the access hole 1122 in the distal end of the cone as well as creating a circumferential lip of paper 1123 as opposed to completely sealing the cone either by a full button fold or by twisting the paper of the cone closed. One benefit is that the hole provides an access point for a needle that can then be inserted into the cone to fill the cone with a fluid core but without having the needle pierce through layers of cone paper. It was found that attempting to pierce through the layers of paper often displaced the leaves within the cone, or lead to uneven compacting of the leaves which detrimentally affected the burning of the cone. The hole ensures that the needle does not meet excess resistance from the paper, and is able to penetrate the length of the cone, through the leaves, without unnecessarily compacting the leaves or causing the paper to push into and displace the leaves at the top of the cone.

Additionally, the hole allows for the creation airflow through the cone when lighting the filled cone. As a flame is brought proximate to the filled cone, air may be drawn through the cone by creating a vacuum at the small diameter end of the cone, thereby drawing the flame into the cone to contact the leaves and core. That assists in lighting the center of the cone where the fluid core was deposited. Without the hole, when the tip is closed due to a complete fold or twisting closed of the paper, it is difficult to create a vacuum in the unlit cone. When a flame contacts a completely closed tip, it was found that the flame would light the paper, and then migrate, or run, down the side of the cone burning the paper rather than the leaves. While the leaves would eventually light, the run of flame tended to cause uneven lighting of the leaves (e.g. lighting the leaves in the vicinity of the run, rather than uniformly across the diameter of the cone) which contributed to an uneven burn rate for the filled cone. It also meant that the leaves along the outside of the cone (proximate to the paper) would ignited first, leaving the fluid filled core unlit. By adding the hole to the tip of the folded cone, when a vacuum is applied to the cone (drawing air in from the distal end and out through the proximal end), the flame is drawn directly into the center of the cone and into the fluid core, to (particularly where the fluid is a flammable

US 11,130,596 B2

19

oil) reliably light the core and centrally located leaves. That results in burning away of the folded paper first (before the paper of the cone surrounding and holding the leaves), which in turn helps contain the leaves as the cone burns, and it contributes more uniformly lighting and progressive burning of the leaves. It was found that providing a folding tip with the foregoing structure created more reliably uniform folds in the end of the filled cone and simultaneously provided an airflow hole in the paper cone.

Additionally, it was found that even with the access hole, leaves within the cone would not consistently uniformly light, and there was risk of flame running down the length of the cone. However, by forming the circumferential lip of paper, as the flame is drawn into the cone through the access hole, it lights the more flammable circumferential lip of paper concurrently. That is, the circumferential lip of paper provides a mass of material, more flammable than the leaves and which mass of material surrounds the distal end of the cone such that the paper lights the circumference of the distal end and forms a strong, uniform cherry at distal end while preventing flame from running down the side of the cone.

In one embodiment, after the cone is folded but while the folding tip remains proximal to the folded top of the cone, injector needle **605** may be extended into the cone, either piercing the folded top or, when the preferred folding tip with axial pin is used to fold the top, passing through the hole formed around the axial pin. The injector needle may be formed coaxially with the folding tip and extend through the folding tip. With reference to FIGS. 6F-6G, the injector needle **605** is inserted into the distal end of leaf filled, folded, cone **1120**. Generally, it has been found that inserting the needle approximately 80% of the length of the cone yields optimal results. Inserting the needle too far results in fluid placement too close to the proximal end, and can cause fluid to oversaturate the proximal end of the cone. If the fluid is not inserted far enough, then the benefits of the fluid are not fully appreciated as the product is used. In FIG. 6G, the injector needle **605** is extracted, and as the needle is extracted, a fluid **1124**, such as an oil, is extruded from the needle and into the filled cone **1120**. In one embodiment an actuator applies variable pressure such to extrude a variable amount of fluid as the needle is extracted. Preferable less pressure toward the distal end of filled cone **1120**, with increasing pressure as the needle is further extracted and progresses toward the distal end of filled cone **1120**. When a tapered cone is being injected with fluid, this allows less fluid to be deposited toward the proximal end of the cone where the cone is narrower and more fluid to be deposited toward the thicker distal end of the cone.

In one embodiment, after folding is complete, (and in some embodiments after any desired fluid is injected and the needle retracted) the cone conveyor **300** moves the die with the filled, folded cone to a quality control station **800**. For example, the cone conveyor **300** rotates the die **310** holding the filled, folded cone to the quality control station and die actuator **350** separates clamping segments **311**, **312** of die **310** and releases the cone. In one embodiment, a cleaning actuator inserts a cleaning brush into the cavity **313** of the die to ensure that the filled cone is released and to clean the hole in the die. This helps prevent residue from building up within the die which may otherwise cause cones to stick within the die. The cone may be deposited on a quality control hopper **801**.

With reference to FIG. 8, in one embodiment, a quality control station includes one or more sensors that check attributes of the filled cone against preset values stored in the

20

control system and determine whether the filled cone is acceptable. For example, one or more sensors, such as a camera or scale may analyze the shape or weight of the cone. In one embodiment, the quality control hopper **801** of the quality control station temporarily holds the filled cone for inspection by at least one quality control sensor (such as **804**) and includes an exit chute **805**. If the attributes of the cone fall within an acceptable tolerance, the cone is accepted. The cone may be released from the quality control hopper **801** to the exit chute where diverting arm **807** may direct the cone to a conveyor **806** (alternately, the cone may be directed to a packaging container or placed in a sealable package). If the attributes of the cone do not fall within an acceptable tolerance, a diverting arm **807** may be moved by an arm actuator **808** to block the cone from the conveyor. The diverting arm diverts the cone into a reject bin **809**. The diverting arm actuator **808** then moves the diverting arm **807** to allow subsequent cones to be deposited onto the conveyor. In another embodiment, the exit chute **805** temporarily holds the filled cone for a further inspection, such as an optical inspection by optical sensors. The cone may then be sent to a conveyor **806** that accommodates the filled cones and allows for further inspection, or, in alternative embodiments, moves the cones for further processing such as core filling. Filled cones may then be accepted or rejected and sent from the conveyor **806** to sealable package containers or the reject bin.

As noted, after an initial quality control check of the cones that are filled with leaves and folded (or in some embodiments without any quality control step, but simply after the cones are filled and folded), the cones are moved by a conveyor, for example conveyor **806**, to an injector station **700**. In such embodiments, the injector needle may be arranged as a separate core injector station.

FIGS. 7A-7D depict various aspects of an embodiment of a separate injector station **700**. As shown in FIG. 1A, an injector station **700**, is arranged apart from the folding station **600** of the packaging system. In one embodiment, filled cones **1120** are transported to a receptacle **701** by conveyor **806**. For example, a conveyor **806** transports the filled cones and deposits each cone in the receptacle **701**. A receptacle actuator **702** may adjust the positioning of the receptacle with respect to the conveyor, such as by tilting it back and forth, to ensure that the cone is deposited properly. In one embodiment, after the cone is deposited, a positioning actuator **703** adjusts the positioning of the receptacle with respect to an injector needle **605**, such as by sliding the receptacle closer to the needle **605**. It should be understood that the needle could alternatively be moved closer to the receptacle, or both could be moved to converge with one another. Also, in place of a receptacle actuator and a positioning actuator, a single multi-axis actuator could be utilized. In a further embodiment, a robotic arm manipulates the position of the receptacle with respect to the conveyor (so that cones from the conveyor are deposited in the receptacle) and the filling station. The robotic arm may further move the receptacle from the filling station to a packaging station **770** where the cone may be placed in a sealable package and, in one embodiment, the sealable package may be purged with an inert gas and sealed. Alternatively another conveyor could be used to move filled cones from the injector station to the packaging station.

The injecting station may further include a needle slide **704**, fluid circuit **720**, fluid pump **731**, one or more heating elements **740**, and a fluid reservoir **750**. The injector station may further include one or more pressure sensors (which may be integrated with valve actuators) that sense the fluid

pressure within the fluid circuit. The injector station may further be equipped with valves, e.g. **761a**, **762a** and valve actuators, e.g. **761b**, **762b**, for actuating the valves to alter the flow of fluid within the fluid circuit. The injector needle **605** is hollow and is positioned coaxially with the needle slide **704**. In one embodiment, the needle slide is also hollow, and includes an access port **705** along its length. The access port is in fluid communication with the hollow needle, such that fluid flowing through the access port may exit through an end of the injector needle **605**. A needle actuator **710**, moves the needle slide within the fluid circuit such that fluid may flow through the access port while the needle slide (and needle) move. Fluid flows through the fluid circuit and into needle slide through the access port **705** and then out through the needle **640**. To control the flow of fluid, the fluid pump **731** operates to pump fluid from the reservoir into the fluid circuit. Working in conjunction with the valves, the fluid pump draws fluid from the reservoir into the fluid circuit by applying negative pressure to the fluid circuit (including the fluid reservoir **750**), the fluid pump then applies positive pressure to the fluid circuit to force fluid to flow through the access port **705** and thus through the needle as the needle is retracted from the cone, thereby depositing a core of fluid within the cone. Just prior to the needle exiting the top of the cone, for example while 0.5 cm of the needle remains within the cone, the fluid pump **731** (which may work in conjunction with the valves), stops applying positive pressure to the fluid circuit and instead applies negative pressure to the fluid circuit thereby retracting fluid back up the needle (thereby preventing fluid from leaking out of the tip of the needle) and again drawing fluid out of the reservoir. The core-filled cone may then be removed from the receptacle, transferred and deposited in a second quality control station, the structure of which is similar to the quality control station **800**, or may be sent to a packaging station **770** and sealed in a package.

To enhance the accuracy of the core filling, heating elements **741**, **742**, **743**, **744**, and **745** maintain proper temperature of the fluid within the fluid circuit and reservoir, thereby maintaining consistent viscosity of fluid. One or more sensors may monitor the temperature, and feedback temperature data to the control system. Additionally, pressure sensors (which may be integrated with the valves, or alternatively pressure data may be derived from the operation of the fluid pump) may transmit pressure data respecting the pressure of the fluid within the fluid circuit. By correlating one or more of the pressure data and temperature data with data respecting inherent properties of the fluid being pumped (where data respecting such inherent properties are stored in the control system) the control system determines the appropriate control of the pressure pump **731** to apply the correct pressure during the cone filling injection to ensure a uniform core fill in each cone.

While each process in the packaging assembly may be conducted separately and independently, they may also be combined and used together to form a filled cone. In one embodiment, the control system operates the actuators to successively perform operation on successive cones. The following is an example of the control system operating to fill a single cone and is described in connection with the flowchart of FIG. 9. The following description is of an embodiment that includes leaves within in the hopper **401**, and where at least one stack of cones is deposited in carousel **200** (though it should be understood that more or less cones could be present). It should also be understood that while the steps are recited separately for explanatory purposes, various steps may be performed simultaneously. More or less

steps could also be utilized depending on the configuration of the packaging system and the desired output product.

In the process at **901**, the rod actuator **250** rotates the carousel **200** with a cone stack **1100a** to orient a cone **1100** above a die **310**. At **902** the hole actuator **260** temporarily releases support of the cone stack **1100a** and a cone is forced through the hole **236** into the die **310** and the hole actuator **260** reengages the cone stack. At **903**, de-nesting fingers **361**, **362** may grip cone **1100** and assist in forcing it through hole **236**. The sensor **367** of the de-nesting fingers determines if a cone is gripped **903a**. If no cone is gripped **903c**, the sensor **367** sends a signal to the control system. The system will attempt to grab a cone three times **903d**. If it is not the third try **903e**, the de-nesting fingers will try to grab a cone again. If it is the third try **903f**/the control system will rotate the carousel (see **901**) to move a new stack of cones into alignment and attempt the process again. If no signal is sent **903b**, indicating a cone was grabbed and deposited into the cone die, then at **904** cone conveyor actuator **303** moves the cone conveyor **300** and the die **310** into position underneath the packer head **570** and funnel **550**, aligning the open distal end of the cone with the exit hole **551** in the funnel **550**. At **905** cone support actuator **562** raises the cone support **561** and cone **1100** to the proper height and packer head **570** with funnel **550** may be lowered onto the die **310**. At **906** the leaves are deposited into the weigh station **510**. The weigh station sensor **511** sends a signal to the control system indicating, for example, the weight of the leaves. The control system assess whether the weight is within tolerance **906a**, such as by checking the sensor signal against a preset value stored in memory, if it is not, the sensor continues to check the weight as leaves are added. If it is **906b**, then at **907** one or more weigh station actuators **514** move the outlet doors **512**, **513** to drop the leaves into the packer head **570** and funnel **550**. As the leaves fall through the funnel and into the cone, at **908**, the packing rod successively applies bursts of pressurized gas. At **909** cone conveyor actuator **303** moves the cone conveyor **300** and the die **310** into position underneath the folder station **600** and aligns the cone with the folder tip **604** as vacuum removes excess leaves in the packer head. At **910**, support actuator **562** raises cone support **561** and filled cone **1120**. At **911** the actuators **643**, **653** move the folding fingers **642**, **652** toward the folding block **620** and the folding tip **604** descends onto the distal end of the cone. At **912**, the folding fingers **642**, **652** pre-fold the distal end of the cone and the cone is drawn through the fingers. At **913**, the folding rod actuator **610** forces the folding tip **604** into the top of the pre-folded cone, and the folder tip presses the top of the pre-folded cone into the die **310** to complete the fold of the distal end of the cone. At **913**, injector needle **605** is inserted into the cone. At **914**, the needle is withdrawn as fluid is injected into the leaf filled cone. At **915** the cone conveyor **300** rotates and moves the die **310** to the quality control station and deposits the cone in the quality control hopper **801**. At **916** sensors determine if the filled cone meets proper specification **916a**. If it is within tolerance **916b**, the filled cone is diverted **917a** to an acceptance conveyor. If it is not **916c**, the cone is diverted **917b** to a reject bin. In an alternate embodiment, the needle and filling steps (**913**, **914**) may occur after the quality control steps (**916**, **917**), and in some embodiments the quality control steps (**916**, **917**) may be repeated multiple times for a single cone. Also with respect to the pumping of fluid into the cone, the control system may monitor the temperature and pressure of the fluid and adjust the tem-

US 11,130,596 B2

23

perature, pressure, or both based on empirical data to maintain consistent flow through the needle and into the cone.

FIG. 10 is a schematic of an embodiment of a control system that is configured to control the various assemblies of the packaging apparatus. It includes a main controller 1000 having a memory 1001, input/output 1002, and a CPU 1003. The I/O 1002 may be connected to one or more I/O devices 1005 such as a display, keyboard, mouse, touchscreen, etc. The various actuators of the system may be connected to the main controller. It should be understood that the main controller could be a single computer that handles all of the signal processing or multiple computers networked together and may further include hardwired circuit controllers as well. The main controller sends signals to the actuators of the system to control the operation of the operators. For pneumatic actuators, the main controller may be connected to a series of valves and actuate valves associated with the actuators to cause the actuators to actuate. It should also be understood that the actuators (for example, in the case of the use of a servo motor) may send feedback signals to the main controller which the main controller may use to further control the operation of the actuators or the actuators may be equipped with additional sensors to monitor their operation and send feedback to the main controller. The sensors of the system may also be connected to the main controller and send feedback to the main controller which the main controller may use to control the operation of one or more actuators. The heating elements, such as heating element 740, may be connected to and controlled by the main controller. The heating elements may further include sensors that sense the temperature of the heating elements and send feedback signals to the main controller regarding the operation of the heating elements that the main controller may use to adjust the temperature.

Although the present invention has been described in terms of various embodiments, it is to be understood that such disclosure is not intended to be limiting. Various alterations and modifications will be readily apparent to those of skill in the art. For example, while the embodiments shown depict the various components in static arrangement, it is contemplated that each could be structured in a dynamic arrangement such that processes such as depositing cones on the cone conveyor, packing the cones, and injecting the cones occur with the stations moving relative to one another, but remaining stationary relative to the cones. Accordingly, it is intended that the appended claims be interpreted as covering all alterations and modifications as fall within the spirit and scope of the invention.

What is claimed is:

1. A folded package comprising:

a hollow paper cone having an exterior, an interior, a length, a center axis along the length, a width, and two ends opposite each other joined by a middle section, where one end is a proximal end, and the other end is a distal end and where the length is greater than the width;

a filling within the cone;

wherein the distal end comprises approximately a quarter of the length of the cone;

wherein the distal end of the cone terminates at a rim; wherein a portion of the distal end is crimped in on itself and folded into the interior of the cone such that the rim of the distal end is held by plastic deformation of the paper within the interior of the cone and forms a circumferential lip of paper at the distal end; and

24

wherein the portion of the distal end that is crimped in on itself and folded into the interior of the cone is folded such that the folded portion of the distal end extends away from the exterior of the cone and into interior of the cone and forms an access hole located along the center axis of the cone.

2. The folded package as in claim 1, wherein the access hole has a diameter that is less than the width of the distal end at every point along the length of the distal end.

3. The folded package as in claim 2, wherein the filling comprises plant matter and a core of fluid, the core of fluid being formed along the center axis and separated from the paper cone by the plant matter.

4. The folded package as in claim 3, wherein the volume of fluid comprising the core varies along the length of the cone.

5. The folded package as in claim 4, wherein the volume of fluid comprising the core is greater toward the distal end of the cone than it is toward the proximal end of the cone.

6. The folded package as in claim 1, wherein the portion of the distal end that is crimped in on itself and folded into the interior of the cone such that the folded distal end extends horizontally from the exterior of the paper cone.

7. The folded package as in claim 3, wherein the core is present along only a portion of the length of the cone.

8. The folded package as in claim 1, wherein the diameter of the access hole is less than the width of the paper cone at every point along the length of the paper cone.

9. A folded package comprising:

a hollow paper cone having an exterior, an interior, a length, a width, and two ends opposite each other joined by a middle section, where one end is a proximal end, and the other end is a distal end and where the length is greater than the width; and

a filling within the cone;

wherein the distal end comprises approximately a quarter of the length of the cone;

wherein the distal end of the cone terminates at a rim; and wherein a portion of the distal end is crimped in on itself and folded into the interior of the cone such that the rim of the distal end is held by plastic deformation of the paper within the interior of the cone such that the folded portion of the distal end substantially covers the filling within the cone and forms a circumferential lip of paper at the distal end.

10. The folded package as in claim 9, wherein an access hole has a diameter that is less than the width of the distal end at every point along the length of the distal end.

11. The folded package as in claim 10 and including a filling, wherein the filling further comprises plant matter and a core of fluid, the core of fluid being formed along the length of the cone and separated from the paper cone by the plant matter.

12. The folded package as in claim 11, wherein the volume of fluid comprising the core varies along the length of the cone.

13. The folded package as in claim 12, wherein the volume of fluid comprising the core is greater toward the distal end of the cone than it is toward the proximal end of the cone.

14. The folded package as in claim 11, wherein the core is present along only a portion of the length of the cone.

15. The folded package as in claim 9, wherein the portion of the distal end that is crimped in on itself and folded into the interior of the cone such that the folded distal end extends horizontally from the exterior of the paper cone.

US 11,130,596 B2

25

16. A folded package comprising:
a hollow paper cone having an exterior, an interior, a length, a center axis along the length, a width, and two ends opposite each other joined by a middle section, where one end is a proximal end, and the other end is a distal end and where the length is greater than the width; and
a filling within the cone;
wherein the distal end comprises approximately a quarter of the length of the cone;
wherein the distal end of the cone terminates at a rim; and folded into the interior of the cone such that the rim of the distal end is held by plastic deformation of the paper within the interior of the cone such that the folded portion of the distal end covers the filling within the cone and forms a circumferential lip of paper at the distal end; and
wherein the folded portion of the distal end that covers the filling within the cone is pierced such that an air

26

passage through the folded portion of the distal end covering the filling is formed between the exterior of the cone and the interior of the cone.
17. The folded package as in claim 16, wherein the air passage has a diameter that is less than the width of the distal end at every point along the length of the distal end.
18. The folded package as in claim 17, and including a filling, wherein the filling comprises plant matter and a core of fluid, the core of fluid being formed along the center axis and separated from the paper cone by the plant matter.
19. The folded package as in claim 18, wherein the volume of fluid comprising the core varies along the length of the cone.
20. The folded package as in claim 19, wherein the volume of fluid comprising the core is greater toward the distal end of the cone that it is toward the proximal end of the cone.

* * * * *

EXHIBIT B



Aronberg Goldgehn Davis &
Garmisa
330 North Wabash Ave., Suite
1700
Chicago, Illinois 60611-3586
TEL: 312-755-9600
FAX: 312-828-9635
www.agdglaw.com

M. "Chip" De Preter
DIRECT: 312-755-3153
DIRECT FAX: 312-222-6364
cdepreter@agdglaw.com

October 19, 2021

SENT PURSUANT TO FRE 408

Via Email and US Certified Mail

Custom Cones USA
7059 S. 190th St.
Kent, WA 98032
Contact@CustomConesUSA.com

RE: US Patent No. 11,130,596

To Whom It May Concern:




We represent MPI, LLC, the owner of US Patent No. 11,130,596 (the " '596 Patent") a copy of the '596 Patent is enclosed herewith for your review. MPI takes the protection and enforcement of its intellectual property seriously. The '596 Patent is directed to folded packages, including filled pre-rolled cones. It has recently come to our attention that Custom Cones USA is at least using and offering to sell, if not actually selling, a machine specifically designed to manufacture folded packages. Particularly, we refer to the "Automated Infused Pre-Roll Machine" (the "Machine") featured at <https://customconesusa.com/automated-infused-pre-roll-machine/> as well as on YouTube at <https://www.youtube.com/watch?v=xRY1DIUCKQQ>. Upon our review of the Machine, we have reason to believe that it infringes one or more claims of the '596 Patent.

Pursuant to 35 U.S.C. § 271(a) whoever without authority makes, uses, offers to sell, or sells any patented invention, within the United States or imports into the United States any patented invention during the term of the patent therefor, infringes the patent. Under 35 U.S.C. § 271(b) anyone that induces another to infringe a patent is also liable as an infringer. Finally, under 35 U.S.C. § 271(c) anyone that offers to sell, sells, or imports a machine (or component thereof) that is especially made or adapted for use in infringement of a patent, and not having a substantial non-infringing use, is liable as an infringer.

After reviewing the structure, operation, and output of the Machine, we believe that the Machine produces folded packages that infringe at least claims 9, 10, and 11 of the '596 Patent

and that the Machine itself is especially adapted to manufacture infringing packages without a substantial non-infringing purpose.

For Example:

<p>US Patent No. 11,130,596</p>	<p>Packages Made Using the Machine (all images from https://customconesusa.com/buy-pre-rolled-cones/ and https://customconesusa.com/automated-infused-pre-roll-machine)</p>
<p>9. A folded package comprising:</p>	
<p>a hollow paper cone having an exterior, an interior, a length, a width, and two ends opposite each other joined by a middle section, where one end is a proximal end, and the other end is a distal end and where the length is greater than the width; and</p>	 


a filling within the cone;




wherein the distal end comprises approximately a quarter of the length of the cone;



wherein the distal end of the cone terminates at a rim; and



wherein a portion of the distal end is crimped in on itself and folded into the interior of the cone such that the rim of the distal end is held by plastic deformation of the paper within the interior of the cone such that the folded portion of the distal end substantially covers the filling within the cone and forms a circumferential lip of paper at the distal end.




Crimped, folded in on itself, held by plastic deformation, substantially covers filling



Circumferential Lip at Distal End

10. The folded package as in claim 9, wherein an access hole has a diameter that is less than the width of the distal end at every point along the length of the distal end



Access hole with diameter smaller than distal end

11. The folded package as in claim 10 and including a filling, wherein the filling further comprises plant matter and a core of fluid, the core of fluid being formed along the length of the cone and separated from the paper cone by the plant matter.



Plant Matter
Filling

Fluid Core,
Separate from
Paper

“a rod of oil is perfectly placed in the center of the pre-roll” see <https://customconesusa.com/automated-infused-pre-roll-machine/>

We understand that the ‘596 patent only recently issued and that you may not have been aware of it until your receipt of this letter. For at least that reason, we are taking this opportunity to apprise you of its existence and provide you with an opportunity to take measures to ensure that you cease infringing the ‘596 Patent going forward. We are confident that the parties can come to a mutually agreeable arrangement to prevent further infringement without the need to resort to legal action.

Therefore, we request that you stop manufacturing, selling, offering to sell, and promoting the Machine. That includes conducting any further video or in-person demonstrations of the Machine either through the internet (on your website, YouTube, or others) and in-person demonstrations at your place of business, at customer locations, at trade shows, or other locations. We request that you promptly remove, all videos that you (or someone at your direction) has posted of the formation of infringing packages from the internet, such as the videos presently on display at the web locations identified herein. We request that you cease and desist all manufacturing, selling, and offering to sell any folded packages manufactured utilizing the Machine as shown in the videos on your website.



We request that you undertake to accomplish the foregoing immediately. We further request that you provide a response to this letter within ten (10) days confirming that you are undertaking the foregoing measures. To the extent that you require additional time, please provide us with an explanation of what you require and the reasons therefore within the fourteen day time period so that the parties can discuss how best to move forward. As noted above, we are confident that the Parties can come to a mutually agreeable solution to the present infringement issue without Court intervention so that each may continue on their respective businesses.

The foregoing is merely for discussion and exemplary purposes, is not limiting, and is subject to change pending further discovery. It shall not be interpreted as constituting the totality of our analysis, assertions, or claims, and is made without prejudice of any kind.

We look forward to receiving you response.

Best Regards,

A handwritten signature in black ink, appearing to read 'M. Chip De Preter'.

M. Chip De Preter

Encl.

cc (w/ Encl.):
Harrison Bard
Harrison@customerconeusa.com

EXHIBIT C



Aronberg Goldgehn Davis &
Garmisa
330 North Wabash Ave., Suite
1700
Chicago, Illinois 60611-3586
TEL: 312-755-9600
FAX: 312-828-9635
www.agdglaw.com

M. "Chip" De Preter
DIRECT: 312-755-3153
DIRECT FAX: 312-222-6364
cdepreter@agdglaw.com

October 19, 2021

SENT PURSUANT TO FRE 408

Via Email and US Certified Mail

Sorting Robotics, Inc.
7647 Hayvenhurst Ave, Suite 39
Van Nuys, CA 91406
hello@sortingrobotics.com

RE: US Patent No. 11,130,596




To Whom It May Concern:




We represent MPI, LLC, the owner of US Patent No. 11,130,596 (the " '596 Patent") a copy of the '596 Patent is enclosed herewith for your review. MPI takes the protection and enforcement of its intellectual property seriously. The '596 Patent is directed to folded packages, including filled pre-rolled cones. It has recently come to our attention that Custom Cones USA is at least using and offering to sell, if not actually selling, a machine specifically designed to manufacture folded packages. Particularly, we refer to the "Jiko" automated pre-roll infusion robot shown (the "Machine") and described on <https://www.sortingrobotics.com/jiko>. It is our understanding that the same machine is featured as the "Automated Infused Pre-Roll Machine" at <https://customconesusa.com/automated-infused-pre-roll-machine/> as well as on YouTube at <https://www.youtube.com/watch?v=xRY1D1UCKQQ>. Upon our review of the Machine, we have reason to believe that it infringes one or more claims of the '596 Patent.





Pursuant to 35 U.S.C. § 271(a) whoever without authority makes, uses, offers to sell, or sells any patented invention, within the United States or imports into the United States any patented invention during the term of the patent therefor, infringes the patent. Under 35 U.S.C. § 271(b) anyone that induces another to infringe a patent is also liable as an infringer. Finally, under 35 U.S.C. § 271(c) anyone that offers to sell, sells, or imports a machine (or component thereof) that is especially made or adapted for use in infringement of a patent, and not having a substantial non-infringing use, is liable as an infringer.

After reviewing the structure, operation, and output of the Machine, we believe that the Machine produces folded packages that infringe at least claims 9, 10, and 11 of the '596 Patent and that the Machine itself is especially adapted to manufacture infringing packages without a substantial non-infringing purpose.

For Example:

<p>US Patent No. 11,130,596</p>	<p>Packages Made Using the Machine (all images from https://customconesusa.com/buy-pre-rolled-cones/ and https://customconesusa.com/automated-infused-pre-roll-machine); see also  https://www.sortingrobotics.com/jiko</p>
<p>9. A folded package comprising:</p>	
<p>a hollow paper cone having an exterior, an interior, a length, a width, and two ends opposite each other joined by a middle section, where one end is a proximal end, and the other end is a distal end and where the length is greater than the width; and</p>	

	 <p>Works with all Cone and Blunt Sizes</p>
<p>a filling within the cone;</p>	
<p>wherein the distal end comprises approximately a quarter of the length of the cone;</p>	 <p>98mm - 3/4 Gram Pre-Rolled Cones</p>

<p>wherein the distal end of the cone terminates at a rim; and</p>	 <p>98mm - 3/4 Gram Pre-Rolled Cones</p>
<p>wherein a portion of the distal end is crimped in on itself and folded into the interior of the cone such that the rim of the distal end is held by plastic deformation of the paper within the interior of the cone such that the folded portion of the distal end substantially covers the filling within the cone and forms a circumferential lip of paper at the distal end.</p>	 <p>Crimped, folded in on itself, held by plastic deformation, substantially covers filling</p>  <p>Circumferential Lip at Distal End</p>
<p>10. The folded package as in claim 9, wherein an access hole has a diameter that is less than the width of the distal end at every point along the length of the distal end</p>	 <p>Access hole with diameter smaller than distal end</p>

11. The folded package as in claim 10 and including a filling, wherein the filling further comprises plant matter and a core of fluid, the core of fluid being formed along the length of the cone and separated from the paper cone by the plant matter.



Plant Matter
Filling

Fluid Core,
Separate from
Paper

“a rod of oil is perfectly placed in the center of the pre-roll” see <https://customconesusa.com/automated-infused-pre-roll-machine/>

We understand that the ‘596 patent only recently issued and that you may not have been aware of it until your receipt of this letter. For at least that reason, we are taking this opportunity to apprise you of its existence and provide you with an opportunity to take measures to ensure that you cease infringing the ‘596 Patent going forward. We are confident that the parties can come to a mutually agreeable arrangement to prevent further infringement without the need to resort to legal action.

Therefore, we request that you stop manufacturing, selling, offering to sell, and promoting the Machine. That includes conducting any further video or in-person demonstrations of the Machine either through the internet (on your website, YouTube, or others) and in-person demonstrations at your place of business, at customer locations, at trade shows, or other locations. We request that you promptly remove, all videos that you (or someone at your direction) has posted of the formation of infringing packages from the internet, such as the videos presently on display at <https://www.sortingrobotics.com/jiko>. We request that you cease and desist all manufacturing, selling, and offering to sell any folded packages manufactured utilizing the Machine.



We request that you undertake to accomplish the foregoing immediately. We further request that you provide a response to this letter within ten (10) days confirming that you are undertaking the foregoing measures. To the extent that you require additional time, please provide us with an explanation of what you require and the reasons therefore within the fourteen day time period so that the parties can discuss how best to move forward. As noted above, we are confident that the Parties can come to a mutually agreeable solution to the present infringement issue without Court intervention so that each may continue on their respective businesses.

The foregoing is merely for discussion and exemplary purposes, is not limiting, and is subject to change pending further discovery. It shall not be interpreted as constituting the totality of our analysis, assertions, or claims, and is made without prejudice of any kind.

We look forward to receiving your response.

Best Regards,

A handwritten signature in black ink, appearing to read "M. Chip De Preter".

M. Chip De Preter

Encl.